

夹持型高扭矩同步带轮 ◀ S3M/S5M/S8M型



同步带轮

19




代码	类型	材质		表面处理	附件
		带轮	法兰		
VPA01	夹持型	铝合金	铝合金	本色阳极氧化	内六角圆柱头螺钉


标准齿型



B向视图



S3M型 (齿距: 3.0)



S5M型 (齿距: 5.0)



S8M型 (齿距: 8.0)

型号			轴孔规格d _{H7} (最小单位1)	P.D.	O.D.	D	F	E	L	V	带轮公称宽		夹紧螺钉							
代码	齿数	种类									A	W	M-长度	紧固扭矩(N·M)						
VPA01	24	S3M060 S3M100	4	22.92	22.16	13	25	16	9	2	皮带宽度6 S3M060 A:7 W:11	M2-8	0.4							
	26			24.83	24.07		28	18												
	28			26.74	25.98		30	20												
	30		6 8	28.65	27.89	20	32	23				皮带宽度10 S3M100 A:11 W:15		M2.5-8						
	32			30.56	29.8		35	25												
	36			34.38	33.62		40	28												
	40		8 10	38.2	37.44	26	44	32	12.5				M3-10	1.5						
	44			42.02	41.25		31	48							36					
	48			45.84	45.07		33	50							38	14	M4-14	3.5		
	50	8 10 11 12 13 14	47.75	46.98	36	52	40													
	60	8 10 11 12 13 14 15 16	57.3	56.53	41	61	46	15.5	M5-16		6									
	24	S5M100 S5M150	8 10	38.2	37.24	26	45	30	12.5		2.5		皮带宽度10 S5M100 A:11 W:16	M3-10	1.5					
	25			39.79	38.83		31	48				35				14	M4-14	3.5		
	26			41.38	40.42			44.56				43.6							52	36
	28			44.56	43.6			52				36								
	30		10	47.75	46.79	55	40	15.5	M5-16			6								
	32		10 11 12 13 14	50.93	49.97	36	55							40						
	34		10 11 12 13 14 15 16	54.11	53.15	41	61							45						
	36		10 11 12 13 14 15 16	57.3	56.34		67							50						
	40		10 11 12 13 14 15 16 17 18 19	63.66	62.7	46	67	50	15.5			M5-16		6						
	44		12 13 14 15 16 17 18 19	70.03	69.07	55	74	58												
	48		20 21 22 23 24	76.39	75.43	46	83	63							16.5	M5-16	6			
	50		20 21 22 23 24 25	79.58	78.62	55	87	67												
	60		12 13 14 15 16 17 18 19	95.49	95.43	46	99	80	15.5			M5-16		6						
	20		20 21 22 23 24 25	50.93	49.56	55	107	87	16.5											
	22		12 13 14	56.02	54.65	41	61	45	16			皮带宽度15 S8M150 A:17 W:22		M4-14	3.5					
	24		12 13 14 15 16	61.12	59.74	46	67	50												
	25	12 13 14 15 16 17 18 19	63.66	62.29	46	70	56													
	28	15 16 17 18 19	71.3	69.93	55	80	60	17					M5-16			6				
	30	20 21 22 23 24 25	76.39	75.02	55	87	67													
	32	15 16 17 18 19	81.49	80.14	46	95	75	17	M5-16					6						
	34	20 21 22 23 24 25	86.58	85.21	55	99	80													
	36	18 19	91.67	90.3	46	107	95	17					M5-16		6					
		20 21 22 23 24 25			55	117	107													



请按图示订货

■ VPA01-22-S8M250-d15

型号			轴孔规格dH7(最小单位1)
代码	齿数	种类	
VPA01	20	S8M150	12 13 14
	22	S8M250	12 13 14 15 16



交期Delivery

7天

发货

本产品发货时间不含周日