


无防尘盖式 ◀ 陶瓷轴承



代码	类型	材质		保持架	推荐使用最高温度
		套圈	球体		
BTC01	标准型	ZrO2	ZrO2	PTFE	200°C
BTC02				PEEK	220°C

型号		d	D	B	r ₁	安装尺寸				参考重量 (g)
代码	轴承型号					d _b		r		
				(min)	(max)	d _a (max)	(max)			
标准型 BTC01 BTC02	6800	10	19	5	0.3	12	12.5	17	0.3	4
	6900		22	6			13	20		7
	6000		26	8			13.5	24		14
	6200		30	9			16	26		25
	6300		35	11			16.5	31		40
	6801	12	21	5	0.3	14	14.5	19	0.3	5
	6901		24	6			15	22		8
	6001		28	8			16	26		17
	6201		32	10			17	28		28
	6301		37	12			18	32		46
	6802	15	24	5	0.3	17	17.5	22	0.3	5
	6902		28	7			19	26		12
	6002		32	9			19	30		24
	6202		35	11			20	31		35
	6302		42	13			22.5	37		64
	6803	17	26	5	0.3	19	19.5	24	0.3	5
	6903		30	7			20	28		13
	6003		35	10			21	33		32
	6203		40	12			23	36		52
	6303		47	14			25.5	42		87
	6804	20	32	7	0.3	22	22.5	30	0.3	13
	6904		37	9			24	35		28
	6004		42	12			26	38		52
	6204		47	14			28	42		82
	6304		52	15			28	45.5		110
	6805	25	37	7	0.3	27	35	40	0.3	16
	6905		42	9			29	40		32
	6005		47	12			30.5	43		61
	6205		52	15			32	47		99
	6305		62	17			31.5	55.5		180
	6806	30	42	7	0.3	32	33	40	0.3	18
	6906		47	9			34	45		40
6006	55		13	37			50	89		
6206	62		16	39			57	150		
6306	72		19	36.5			65.5	270		
6807	35	47	7	0.3	37	38	45	0.3	21	
6907		55	10			39	51		58	
6007		62	14			40	57		120	
6207		72	17			41.5	65.5		220	
6307		80	21			43	72		360	
6808	40	52	7	0.3	42	43	50	0.3	20	
6908		62	12			44	58		90	
6008		68	15			45	63		150	
6208		80	18			46.5	73.5		280	
6308		90	23			48	82		490	
6809	45	58	7	0.3	47	47.5	56	0.3	29	
6909		68	12			49	64		97	
6009		75	16			50	70		190	
6209		85	19			51.5	78.5		320	
6309		100	25			53	92		640	
6810	50	65	7	0.3	52	52.5	63	0.3	38	
6910		72	12			54	68		100	
6010		80	16			55	75		200	
6210		90	20			56.5	83.5		350	
6310		110	27			59	101		820	



■ BTC01-6800

型号		d	D	B
代码	轴承型号			
BTC01	6800	10	19	5
BTC02	6900		22	6



交期Delivery

7 天 发货

○本产品发货时间不含周日