



线槽 ◀ PVC方形线槽 标准型/全封闭型




代码	类型	销售方式	材质	颜色	阻燃等级	温度
JDQC01	标准型	米	环保硬质PVC	灰色	UL94V-0	-20°C~+70°C
JDQC11	全封闭型					

特性:开口齿槽, 反扣式槽盖与槽体设计组合后绝不脱落, 且接合面平滑, 不割伤手及擦损附近配线。


JDQC01





W≤60mm线槽底部孔尺寸




W≥80mm线槽底部孔尺寸



JDQC11



W≤60mm线槽底部孔尺寸



W≥80mm线槽底部孔尺寸



型号		W	A	B	销售方式: 米			
代码	H				起订数			
JDQC01 JDQC11	20	20	4	若A尺寸为4, B尺寸则为6	按2的倍数起订			
		25						
	25	25						
		30						
		35						
		40						
		30					25	
							30	
	35							
	35	25						
		30						
		35						
	40	25						
		30						
		40					25	
							30	
							35	
		45					25	
							33	
							45	
							50	25
								30
								35
		40						
45								
50								
60	25							
	30							
	35							
	40							
	45							
	50							

型号		W	A	B	销售方式: 米		
代码	H				起订数		
JDQC01 JDQC11	45	45	4 6 8	若A尺寸为4, B尺寸则为6	按2的倍数起订		
		50					
		60					60
							80
							100
							120
	65						25
							33
		35					
		45					
		65					
		65					
	80	25					
		30					
		35					
		40					
		45					
		50					
	100	55					
		60					
		80					
		100					
		120					
		35					
40							
50							
60							
80							
100							

波纹管
发热管
16



请按图示订货

JDQC01-W20-H20-A4

型号			
代码	W	H	A
JDQC01	20	20	4



交期Delivery

5天 发货

○本产品发货时间不含周日