




磁力轮 ◀ 平行传动磁力轮



代码	类型	材质		表面处理		使用温度
		支架	磁环	支架	磁环	
FZQ21	直交锥传动型	AL6061	钕烧结体	阳极氧化	镀镍	0~80





型号	A	B	C	D	E	F	传动比	间隙1mm时扭矩(N.m)	间隙5mm时扭矩(N.m)
FZQ21	30	26	8/10/12/15	8/10/12/15	16	21	1比1	0.45	0.04
	35	30	8/10/12/15	10/12/15/16	16	20	5比4	0.7	0.06
	47	35	10/15/20	10/12/15/20	21	25	1比1	1.3	0.18
	60	45	15/20/25	15/20/25	25	30	1比1	2.5	0.34
	65	45	15/18/20/25	15/20/25	24	30	1比1	3.9	0.8
	75	52	18/20/25	15/20/25/30	27	33	1比1	5.6	1.1

磁力齿轮 ◀ 同轴平面传动



代码	类型	材质		表面处理		使用温度
		支架	磁环	支架	磁环	
FZQ31	同轴平面传动型	AL6061	钕烧结体	阳极氧化	镀镍	0~80



型号	A	B	C	D	E	F	G	H	M	间隙1mm时扭矩(N.m)	间隙5mm时扭矩(N.m)
FZQ31	12	4/5/6	16	12	/	/	/	/	3	0.005	/
	24	6/8/10	18	18	10	5	6	3.2	4	0.42	0.04
	28	6/8/10	18	20	10	5	10	4.2	4	0.75	0.12
	32	8/10/12	18	24	10	5	12	4.2	5	1.95	0.32
	38	8/10/12/15	18	28	10	5	15	5.2	5	2.98	0.82
	43	12/15/20	20	30	12	5	15	5.2	5	3.8	1.2
	50	12/15/20	22	34	13	6	20	5.2	5	4.2	1.5
	63	15/18/20/25	25	36	15	6	26	5.2	5	11	4.5
	68	15/18/20/25	30	40	18	8	30	6.2	5	16.2	7.8
	78	18/20/25/30	32	42	18	10	33	6.2	5	18.5	10



请按图示订货

■ FZQ21-A35-B30-C10-D12

型号	A	B	C	D
代码				
FZQ21	35	30	8/10/12/15	10/12/15/16

■ FZQ31-A32-B10

型号	A	B
代码		
FZQ31	32	8/10/12