




加厚T型导向轴支座 ◀ 分离型



代码	类型	材质		表面处理	附件
		国标	相当		
ZFE01	分离型	45	S45C	发黑	2个内六角圆柱头螺钉 (不锈钢)
ZFE02				无电解镀锌	
ZFE06		0Cr18Ni9	SUS304	/	
ZFE08		LF2	A5052	本色阳极氧化	

- 1.开口型, 安装孔D的公差H7为开口加工前的公差, 开口加工后由于有内部应力释放, 公差有可能增至H8左右, 不影响客户使用。
- 2.如防锈有要求, 请优先选用不锈钢材质、铝合金材质或喷细砂无电解镀锌产品。



型号			H				L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N													
代码	D _{H7}																																
ZFE01 ZFE02 ZFE06 ZFE08	8	+0.015 0	(10) (15) (20)	25 30 40	62	H+10	15	7.5	5.8	37.8	50	6.6	23	M6深12	6.6	11	6.6	2															
	10		(10) (15) (20)	25 30 40 50 60		H+11							24																				
	12		(10) (15) (20)	25 30 40 50 60		H+12	18	9																									
	13	+0.018 0	(15) (20)	25 30 40 50 60		H+14	20	10																									
	15		(15) (20)	25 30 40 50 60																													
	16		(15) (20)	25 30 40 50 60																													
	20	+0.021 0	(20)	25 30 40 50 60 80	85	H+18	25	12.5	7.8	52.8	70	9	36	M8深16	9	14	9																
	25		(20) (25)	30 40 50 60 80			30	15																									
	30		(25)	30 40 50 60 80			H+30	35	17.5				48																				
	35	+0.025 0	(25)	30 40 50 60 80	110			40	20	9.8	69.8	90	6.6																				
	40			30 40 50 60 80																													
	50				40 50 60 80	154	H+40	50	25				14.8	101.8	128	11	76		N12深25	14	20	13											

■带()的H尺寸对应的螺孔M底孔贯通;可能出现螺孔M底孔贯穿的情况。



请按图示订货

■ ZFE01-D8-H25

型号			H
代码	D _{H7}		
ZFE01	8	+0.015 0	25



交期Delivery

6天

发货

○本产品发货时间不含周日