


滚珠丝杆
花键／支座组件



代码	技术说明
----	------

代码	技术说明
----	------

增加固定侧轴端键槽	选型方法 HG8
-----------	----------

11-12	4	-0.03	2.5
-------	---	-------	-----

HH()  (固定側)	増大固定側軸端鍵槽 选型方法 HH5-S2 ●最小单位1 ●HH值+S值≤23, 鍵槽寬<HH值 <table border="1"> <thead> <tr> <th>P</th><th>b</th><th>t</th></tr> </thead> <tbody> <tr> <td>8~10</td><td>3 -0.004 -0.029</td><td>1.8</td></tr> <tr> <td>11~12</td><td>4 -0.003</td><td>2.5 +0.1 0</td></tr> </tbody> </table>	P	b	t	8~10	3 -0.004 -0.029	1.8	11~12	4 -0.003	2.5 +0.1 0
P	b	t								
8~10	3 -0.004 -0.029	1.8								
11~12	4 -0.003	2.5 +0.1 0								

[illegible]

HJ()	增加固定侧轴端平面(1处) 	选型方法 HJ10 ●最小单位1 ●$5 \leq HJ \text{ 值} \leq 23$
--------------	--	--

HK ()  HK () 位置 90°	增加固定侧轴端平面(2处) (固定侧)  HK () 位置 0°	选型方法 HK8 ●最小单位1 ●$5 \leq \text{HK值} \leq 23$
--	---	--

