


平皮带用惰轮 ◀ 法兰型/圆弧型 H=6-32




代码	类型	材质		表面处理	附件
		主体	轴承		
VBG01	法兰型	45	S45C	发黑	挡圈 (SUS304)
VBG02		LF2	A5052	无电解镀锌	
VBG04		0Cr18Ni9	SUS304	本色阳极氧化	
VBG11		45	S45C	发黑	
VBG21	圆弧型	45	S45C	无电解镀锌	
VBG22		LF2	A5052	本色阳极氧化	
VBG24		0Cr18Ni9	SUS304	本色阳极氧化	
VBG31		蓝色POM	蓝色POM	/	


■如对防锈有要求，请优先选用不锈钢材质或无电解镀锌产品。
轴承采用压入式；轴承精度：GB/T307.10级，相当于：JISB15140级，

法兰型 VBG01/02/04/11

H=6·11




H=16·21·27·32




圆弧型 VBG21/22/24/31/36

H=11



H=16·21·27·32



■ 法兰型

型号	代码	D	H	P	dh	V	L	使用轴承
								型号 d B
VBG01 VBG02 VBG04 VBG11	15	6	11	9	2	8	694ZZx1	4 4
	20	6	16	13	1.5	8	625ZZx1	5 5
	25	11	19	16	4	13	626ZZx1	6 6
	30	11	19	17	3.5	13	698ZZx1	8 8
	15	16	11	9	1.5	18	685ZZx2	5 5
	20	16	16	13	4	18	625ZZx2	6 6
	25	16	19	16	3.5	18	626ZZx2	8 8
	30	16	19	17	3.5	18	698ZZx2	10 10
	35	26	23			23	6000ZZx2	10 8
	40							
	15	21	11	9	1.5	23	685ZZx2	5 5
	20	21	16	14	4	23	688ZZx2	8 6
	25	21	19	17	3.5	23	698ZZx2	10 8
	30	21	26	23	3.5	23	6000ZZx2	10 8
	40							
	15	27	11	9	1.5	29	685ZZx2	5 5
	20	27	16	14	4	29	688ZZx2	8 6
	25	27	19	17	3.5	29	698ZZx2	10 8
	30	27	26	23	3.5	29	6000ZZx2	10 8
	40							
	15	32	11	9	1.5	34	685ZZx2	5 5
	20	32	16	14	4	34	688ZZx2	8 6
	25	32	19	17	3.5	34	698ZZx2	10 8
	30	32	26	23	3.5	34	6000ZZx2	10 8
	40							
	50							

■ 圆弧型

型号		H	P	dh	V	使用轴承					
代码	D					型号	d	B			
VBG21 VBG22 VBG24 VBG31 VBG36	20	11	16	13	3	625ZZx1	5	5			
	25		16	2	626ZZx1	6	6				
	30		17		698ZZx1	8					
	15	16	11	9	—	685ZZx2	5	5			
	20		16	13		625ZZx2					
	25		19	16		626ZZx2	6	6			
	30			17		698ZZx2	8				
	35		26	23	—	6000ZZx2	10	8			
	40										
	15	11				9	685ZZx2	5	5		
	20	16	14	688ZZx2	8	6					
	25	21	19	17			698ZZx2				
	30				698ZZx2						
	35	26	23	—	6000ZZx2	10	8				
	40										
	50	27	28	25	6001ZZx2	12	5				
	15		11	9	685ZZx2	5					
	20		16	14	688ZZx2	8		6			
	25		19	17	698ZZx2						
	30	27	26	23	—	698ZZx2	10	8			
	40					6000ZZx2	12				
	50					28	25		6001ZZx2		
	15					11	9		685ZZx2	5	5
	20	16	14	688ZZx2	8	6					
	25	32	19	17			—	698ZZx2	10	8	
	30				6000ZZx2	12					
	40				26	23		6001ZZx2			
50	28				25	685ZZx2		5			
15	32	16	14	—	688ZZx2	8	5				
20					698ZZx2			10			
25					19	17		—	6000ZZx2	12	8
30									6001ZZx2	12	

■ 可选加工项

可选加工	切割法兰	变更法兰厚度
代码	FC()	TC
技术说明	选型方法 FC18.5 ■降低法兰高度。 ■最小单位0.5。 ■D≤FC<D+4 ■仅适用法兰型。	选型方法 TC ■将法兰厚度变更为0.5。 ■L尺寸缩短1mm。 ■仅适用法兰型。



请按图示订货

■ VBG01-D20-H11-FC

型号	代码	D	H	可选加工代码
VBG01	20	11		FC() TC



交期Delivery

7天

发货

○本产品发货时间不含周日