




圆皮带用滑轮 ◀ 夹紧型/梯形槽



代码	类型		材质		表面处理
			国标	相当	
VBS01	夹紧型	梯形槽	45	S45C	发黑
VBS11			LF2	A5052	本色阳极氧化



6.3/

■M=M3时, d₁=Ø6.5 d₂=Ø3.3
M=M4时, d₁=Ø8 d₂=Ø4.3

型号		皮带半径	dH7选择	D	D1	D2	h	W	L	T	T1	V	X	Y	M	适用 皮带直径				
代码	A																			
VBS01 VBS11	20	1	4 5	16	22	18	1	2.2	11	5	2.5	2.5	5	3	M3	2				
	30		4 5 6 6.35 8	20	32	28							7	3.5						
	40				42	38														
	30	1.5	4 5 6 6.35 8	20	32	27	1.5	3.3	16	10	5	2.5	7	3.5	M3	3				
	40				42	37														
	45		4 5 6 6.35 8 10 11 12	25	47	42							4.5	9	4.5		M4			
	60				62	57														
	23	2	4 5 6 6.35 8	20	25	19	2	4.4	16	10	5	2.5	7	3.5	M3	4				
	28				30	24														
	30				32	26														
	40		4 5 6 6.35 8 10 11 12	25	42	36			20				4.5	9	4.5		M4			
	45				47	41														
	48				50	44														
	60	2.5	4 5 6 6.35 8 10 11 12	25	62	56	2.5	5.5	20	10	5	2.5	7	3.5	M3	5				
	80				82	76														
	28				30	23														
	40				42	35														
	48				50	43														
	50				52	45														
	60	3	4 5 6 6.35 8 10 11 12	25	62	55	3	6.6	20	10	5	2.5	7	3.5	M3	6				
	75				77	70														
	80				82	75														
	28				30	22														
	38				40	32														
	48				50	42														
	50				52	44														
	58				60	52														
	60	3			62	54														
	75				77	69														
	95				97	89														
	100				102	94														



请按图示订货

■ VBS01-A20-1-d6

型号		皮带半径	dH7选择
代码	A		
VBS01	20	1	4 5



交期Delivery

6天

发货

○本产品发货时间不含周日