


圆皮带用惰轮 ◀ 窄幅型/标准型/外螺纹型




代码	类型	主体			外螺纹			轴承
		材质		表面处理	材质		表面处理	材质
		国标	相当		国标	相当		
VB01	窄幅型	45	S45C	发黑	/	/	/	钢
VB02				无电解镀锌				
VB11		LF2	A5052	本色阳极氧化				
VB21				/				
VB51	外螺纹型	45	S45C	发黑	45	S45C	发黑	钢
VB52				无电解镀锌				
VB61		LF2	A5052	本色阳极氧化				
VB71				/				
		0Cr18Ni9	SUS304	/	0Cr18Ni9	SUS304	/	不锈钢


■如防锈有要求，请优先选用不锈钢材质或无电解镀锌产品。

■轴承精度：GB/T 307.1 0级
相当于：JIS B 1514 0级

标准型
VB01/02/11/21



外螺纹型
VB51/52/61/71



6.3/

■轴承为粘接式。
■外螺纹部销为铆接。

型号		R	F	d	P	D	D1	B	标准轴承	M	G	F1	适用			
代码	A												圆皮带直径			
标准型 VBU01 VBU02 VBU11 VBU21	(15)	1.1	—	4	11	17	13	4	BAF694ZZ	—	—	—	2			
	(20)				13	21	18		BAF624ZZ							
	(30)				5	16	32		28					BAF625ZZ		
	(20)	1.6		4	13	22	17		BAF624ZZ				3			
	(23)				16	25	20		BAF625ZZ							
	(30)				20	32	27		BAF685ZZ							
	(18)	2.1	8	6	15	25	19	BAF696ZZ	M6	3	1.0	4				
	23				19	30	24	BAF626ZZ								
	28				32	26	BAF698ZZ									
	30		12	12	24	42	36	6	M10	6	1.5					
	40					50	44									
	48					30	23						BAF626ZZ	M6	3	1.0
外螺纹型 VBU51 VBU52 VBU61 VBU71	40	2.6	8	8	19	42	35	BAF698ZZ	5							
	48				50	43										
	50				52	45	BAY6901ZZ	M10		6	1.5					
	38	3.1	10	8	24	40	32		8			BAF628ZZ	M8	4	1.0	6
	48				50	42										
	50				52	44	BAY6001ZZ									
	60		12	12	28	62	54	9	BAY6904ZZ	M10	6	1.5				
	100				20	37	102						94			
	50				52	42	10						BAY6201ZZ			
	60	62		50	12	BAY6004ZZ										
	80	42		82			70									
	(140)	5.1		20			42	142	130				12	—	—	—

■带()的尺寸不适用于外螺纹型



请按图示订货

■ VB01-A20-R1.1

型号	R
代码	A
VB01	20
	1.1



交期Delivery

6天

发货

○本产品发货时间不含周日