



定位珠 ◀ 角座型无弹簧定位珠/动向钢珠定位螺钉·螺钉型





代码	类型		主体			挡块	
			材质	硬度	表面处理	材质	硬度
YZN21	无弹簧 定位珠	角座型	SCM435	38-43HRC	发黑	SUJ2	55HRC~
YZN23			SUS304	-	-	SUS440C	
YZX01	动向钢珠 定位螺钉	平面型	S45C	28~32HRC	发黑	SUJ2	62HRC~
YZX02		齿型					


角座型
YZN21/23



平面型
YZX01



齿型
YZX02



型号		L					d	K	V	H	耐负载(kN)
代码	M										
		4	6	10	16		2	2	2	0.3	1.3
YZN21	5	8	12	20		2.5	2.5	0.4		1.4	
	6	10	16	20	25	3.2	3	3.5	0.6	3.3	
	8	10*	12	20	25	30	4.5	4	5(2.5)	3.9	
	10	12*	16	20	25	35	6	5	6(3.5)	3.4	
YZN23	12	16*	20	30	40	7.2	6	8(3)	1	4.8	
	16	20*	25	35	50	10.7	8	10(3)	1.3	8.9	

注：1.带* L尺寸的V尺寸为()内尺寸。2.kgf=Nx0.101972

型号		L	D	S	T	最大承载力	重量(g)	
代码	M							
		14	10	5	6	9	5.3	
YZX01	6	23					7.4	
		33					9.5	
		18	13	6	8	15	13.5	
		28					20	
38	24							
50	30							
YZX02	8	24	16	8	10	20	26	
		39					34	
		59					46	
YZX01	10	30	18	10	12	30	40	
		45					50	
		65					70	
		80					83	
YZX02	12	39	24	14	16	60	90	
		49					110	
		64					130	
		89					170	
YZX01	16	50	30	17	20	90	185.1	
		80					256.4	
		100					301.2	
YZX02	20	60	36	19	24	120	324.8	
		90					283.5	
		120					351	



请按图示订货

■ YZN21-M4-L15

型号		L				
代码	M	4	10	15	20	30
YZN21	4	10	15	20	30	

■ YZX01-M6-L23

型号		L			
代码	M	6	14	23	33
YZX01	6	14	23	33	



交期Delivery

3天 发货

○本产品发货时间不含周日