


六角螺母 ◀ 标准型/薄型/加厚型 粗牙/细牙




代码	类型	螺纹	材质	表面处理	适用标准	
YWQ11	标准型	细牙	S45C	发黑	GB/T 6171-2000	
YWQ12				镀锌		
YWQ13				/		
YWQ23	薄型	粗牙	SUS304	/	GB/T 6172.1-2000	
YWQ31	加厚型		S45C	镀锌	GB/T 6175-2016	
YWQ33			SUS304	/		


标准型
YWQ11/12/13



薄型
YWQ23



加厚型
YWQ31/33



型号		P 螺距	m	S	e
代码	M		(max)	(max)	(min)
细牙 YWQ11	8	1	6.8	13	14.38
	10		8.4	16	17.77
	12	1.25	10.8	18	20.03
	14	1.5	12.8	21	23.36
	16		14.8	24	26.75
	18		15.8	27	29.56
	20		18	30	32.95
	22		19.4	34	37.29
细牙 YWQ12	24	2	21.5	36	39.55
	10	1	8.4	16	17.77
	12	1.25	10.8	18	20.03
	14	1.5	12.8	21	23.36
	16		14.8	24	26.75
细牙 YWQ13	10	1	8.4	16	17.77
	12	1.25	10.8	18	20.03
	14	1.5	12.8	21	23.36
	16		14.8	24	26.75
	20		18	30	32.95

型号		P 螺距	m	S	e
代码	M		(max)	(max)	(min)
粗牙 YWQ23	2	0.4	1.2	4	4.32
	2.5	0.45	1.6	5	5.45
	3	0.5	1.8	5.5	6.01
	4	0.7	2.2	7	7.66
	5	0.8	2.7	8	8.79
	6	1	3.2	10	11.05
	8	1.25	4	13	14.38
	10	1.5	5	16	17.77
	12	1.75	6	18	20.03
	14	2	7	21	23.36
	16	2	8	24	26.75
	20	2.5	10	30	32.95
	24	3	12	36	39.55
	27	3	13.5	41	45.2
	30	3.5	15	46	50.85
	40	4.5	21	65	71.3

型号		P 螺距	m	S	e
代码	M		(max)	(max)	(min)
粗牙 YWQ31 YWQ33	6*	1	5.7	10	11.05
	8	1.25	7.5	13	14.38
	10	1.5	9.3	16	17.77
	12	1.75	12	18	20.03
	16	2	16.4	24	26.75
	20	2.5	20.3	30	32.95
	24	3	23.9	36	39.55

带*规格仅适用于YWQ33



请按图示订货

■ YWQ11-M8

型号	
代码	M
YWQ11	8



交期Delivery

3 天

发货

○ 本产品发货时间不含周日