



防松动型螺母 ◀ 缩紧锁紧型



代码	类型		材质		热处理	表面处理
			国标	相当		
GYAK02	圆形	缩紧锁紧型	45	S45C	28~32HRC	发黑

- 特点:该产品通过螺母本身的弹性变形,使螺纹面紧密贴合于外螺纹,实现轴向强力紧固。其锁紧能力优异,适用于易松脱、高扭矩、工作条件恶劣的场合。
- 螺纹精度:ISO4H;
- 端面偏摆:0.005



型号	螺距	B	H	d	c	n-b	n-M x L	扭紧力矩 (N·M)
GYAK02	0.75	32	16	29	23	3-4	3-M4 x 10	3.5
	1.0	26	14	25	19	3-3	3-M3 x 10	2.5
		33		30	23.5		4-M4 x 12	
	1.5	37		34	26			
		38			28			
	1.0	40	18	36	30	4-4	4-M4 x 12	
	1.5							
		42		38	32			
		44			34			
		45		41	35			
		46	20	43	37		4-M4 x 14	
		48		45	39			
	1.5	50		47	41	4-5		3.5
		53		50	44			
		56	22	53	47		4-M4 x 16	
		58		55	49			
		60		57	51			
		68		63	57		6-M4 x 16	
		69		65	58			
		70		66	60			
	2.0	72	25	68	62		6-M4 x 18	
	1.5	75		71	65			
	2.0							
	1.5			77	70	6-6		4.5
	2.0							
	1.5		26	79	72		6-M5 x 18	
	2.0							
				82	75			
	1.5						6-M5 x 20	
	2.0							
	1.5			84	77			

型号	螺距	D	H	d	c	n-b	n-M x L	扭紧力矩 (N·M)
GYAK02	2.0	88		84	77	6-6		
	1.5	93		89	80			
	2.0				82	6-7	6-M5 x 20	4.5
	1.5	95						
	2.0			91	84			
	1.5	97						
	2.0			94	87			
	1.5	100						
		110		103	95			
		115		108	100			
		120		113	105			
	2.0	125	32	118	110	6-8	6-M6 x 22	
		130		123	115			
		135		128	120			
		140		133	125			
		145	34	138	130		6-M6 x 22	8
		155		146	136		6-M6 x 25	
		160		150	140		6-M6 x 25	
	3.0	165		156	148		8-M6 x 25	
	2.0	180		168	160		6-M6 x 25	
	3.0						8-M6 x 25	
	2.0	190	38	178	170			
		205		193	182			
	3.0	215		204	193			
		230		216	205		8-M8 x 30	
		240		226	215	8-10	8-M8 x 25	18
		245		234	223		8-M8 x 25	
	4.0			253			8-M8 x 30	
	3.0	265		255	243			
	4.0			253				
		275		265	251			
	3.0	285		270	257			
				275	261			
	4.0	295	42	285	271		8-M10 x 30	35
	3.0	305		295	283	8-12		
		325		315	303			
	4.0	345		335	323			



请按图示订货

GYAK02-M10-0.75

型号	代码	M	螺距
GYAK02		10	0.75



交期Delivery

3天

发货

○本产品发货时间不含周日