


防松动型螺母 ◀ 径向锁紧型 圆形


代码	类型	形状	精度	端面偏摆	材质 国标 相当	热处理	表面处理
GYAK11	精密型	径向 四槽	4H	≤0.002	45	S45C	28~32 HRC
GYAK12	标准型	径向 三槽	4H	0.002~0.005	45	S45C	28~32 HRC
GYAK13	标准型	径向 三槽	4H	0.002~0.005	45	S45C	28~32 HRC



三槽
GYAK12



四槽
GYAK11/13



型号	公称尺寸	螺距	A	H	g	t	d	n-m	扭紧力矩
精密型 GYAK11	M6*	0.5	16	8	3	2	11	2-M4	3.5
	M8*	0.75	18	10	4	2	13	2-M4	3.5
	M10*	1.0	20	12	5	2	16	2-M4	3.5
	M12*	1.25	25	16	8	3	20	2-M4	3.5
	M14*	1.5	30	20	10	4	23	2-M5	4.5
	M16*	1.5	32	22	12	5	25	2-M5	4.5
	M17*	1.0	35	24	14	6	27	3-M5	4.5
	M18*	1.5	38	26	16	8	30	3-M5	4.5
	M20	1.0	42	30	20	10	33	3-M5	4.5
	M22	1.5	45	32	22	12	37	3-M5	4.5
	M24	1.5	50	36	24	14	40	3-M5	4.5
	M25	1.5	55	40	28	16	46	3-M6	8
	M27	1.0	60	45	32	20	52	3-M6	8
	M30	1.5	65	50	36	24	56	3-M6	8
	M33	1.5	70	55	40	28	59	3-M6	8
	M35	1.5	75	60	45	32	62	3-M6	8
	M36	1.5	80	65	50	36	66	3-M6	8
	M38	1.5	85	70	55	40	68	3-M6	8
	M39	1.5	90	75	60	45	73	3-M6	8
	M40	1.5	95	80	65	50	78	3-M6	8
	M42	1.5	100	85	70	55	84	3-M6	8
	M45	1.5	110	95	80	65	86	3-M6	8
	M48	1.5	120	105	90	75	90	3-M6	8
	M50	1.5	130	115	100	80	92	3-M6	8
标准型 GYAK13	M6*	0.5	16	8	3	2	11	2-M4	3.5
	M8*	0.75	18	10	4	2	13	2-M4	3.5
	M10*	1.0	20	12	5	2	16	2-M4	3.5
	M12*	1.25	25	16	8	3	20	2-M4	3.5
	M14*	1.5	30	20	10	4	23	2-M5	4.5
	M16*	1.5	32	22	12	5	25	2-M5	4.5
	M17*	1.0	35	24	14	6	27	3-M5	4.5
	M18*	1.5	38	26	16	8	30	3-M5	4.5
	M20	1.0	42	30	20	10	33	3-M5	4.5
	M22	1.5	45	32	22	12	37	3-M5	4.5
	M24	1.5	50	36	24	14	40	3-M5	4.5
	M25	1.5	55	40	28	16	46	3-M6	8
	M27	1.0	60	45	32	20	52	3-M6	8
	M30	1.5	65	50	36	24	56	3-M6	8
	M33	1.5	70	55	40	28	59	3-M6	8
	M35	1.5	75	60	45	32	62	3-M6	8
	M36	1.5	80	65	50	36	66	3-M6	8
	M38	1.5	85	70	55	40	68	3-M6	8
	M39	1.5	90	75	60	45	73	3-M6	8
	M40	1.5	95	80	65	50	78	3-M6	8
	M42	1.5	100	85	70	55	84	3-M6	8
	M45	1.5	110	95	80	65	86	3-M6	8
	M48	1.5	120	105	90	75	90	3-M6	8
	M50	1.5	130	115	100	80	92	3-M6	8
	M52	1.5	140	125	110	90	94	3-M6	8
	M55	1.5	150	135	120	100	98	3-M6	8
	M60	1.5	160	145	130	110	100	3-M6	8
	M65	1.5	170	155	140	120	102	3-M6	8
	M68	1.5	180	165	150	130	104	3-M6	8
	M70	1.5	190	175	160	140	106	3-M6	8
	M72	1.5	200	185	170	150	108	3-M6	8
	M75	1.5	210	195	180	160	110	3-M6	8
	M76	1.5	220	205	190	170	112	3-M6	8

带*号尺寸不适用于GYAK11

标准型・三槽

代码	公称尺寸	螺距	A	H	g	t	d	n-m	扭紧力矩
精密型 GYAK12	M6	0.5	16	8	3	2	11	2-M4	3.5
	M8	0.75	18	10	4	2	13	2-M4	3.5
	M10	1.0	20	12	5	2	16	2-M4	3.5
	M12	1.25	25	16	8	3	20	2-M4	3.5
	M14	1.5	30	20	10	4	23	2-M5	4.5
	M15	1.0	25	18	8	3	21	2-M5	4.5
	M16	1.5	28	22	10	4	24	2-M5	4.5
	M17	1.0	30	24	12	5	26	3-M5	4.5
	M18	1.5	32	26	14	6	28	3-M5	4.5
	M20	1.0	35	30	16	8	31	3-M5	4.5
	M22	1.5	38	32	18	9	34	3-M5	4.5
	M24	1.5	42	36	20	10	38	3-M5	4.5
	M27	1.0	45	40	22	12	41	3-M5	4.5
	M30	1.5	50	45	24	14	48	3-M5	4.5
	M33	1.5	55	50	26	16	52	3-M5	4.5
	M35	1.5	58	52	28	18	55	3-M5	4.5
	M36	1.5	60	54	30	20	57	3-M5	4.5
	M38	1.5	62	56	32	22	60	3-M5	4.5
	M39	1.5	65	58	34	24	63	3-M5	4.5
	M40	1.5	68	60	36	26	66	3-M5	4.5
	M42	1.5	70	62	38	28	67	3-M5	4.5
	M45	1.5	75	65	40	30	69	3-M5	4.5
	M48	1.5	80	70	42	32	71	3-M5	4.5
	M50	1.5	85	75	44	34	74	3-M5	4.5
	M52	1.5	90	80	46	36	79	3-M5	4.5
	M55	1.5	95	85	48	38	85	3-M5	4.5
	M56	1.5	100	90	50	40	88	3-M5	4.5
	M58	1.5	105	95	52	42	91	3-M5	4.5
	M60	1.5	110	100	54	44	93	3-M5	4.5
	M65	1.5	120	110	60	48	98	3-M5	4.5
	M68	1.5	125	115	62	50	100	3-M5	4.5
	M70	1.5	130	120	64	52	102	3-M5	4.5
	M72	1.5	135	125	66	54	104	3-M5	4.5
	M75	1.5	140	130	68	56	106	3-M5	4.5
	M76	1.5	145	135	70	58	108	3-M5	4.5
	M80	1.5	150	140	72	60	110	3-M5	4.5
	M85	1.5	160	150	78	66	112	3-M5	4.5
	M90	1.5	170	160	84	72	117	3-M5	4.5
	M95	1.5	180	170	90	78	122	3-M5	4.5
	M100	1.5	190	180	96	84	127	3-M5	4.5
	M105	1.5	200	190	102	90	132	3-M5	4.5
	M110	1.5	210	200	108	96	137	3-M5	4.5
	M115	1.5	220	210	114	102	142	3-M5	4.5
	M120	1.5	230	220	120	108	147	3-M5	4.5
	M125	1.5	240	230	126	114	152	3-M5	4.5
	M130	1.5	250	240	132	120	157	3-M5	4.5
	M135	1.5	260	250	138	126	162	3-M5	4.5
	M140	1.5	270	260	144	132	167	3-M5	4.5
	M145	1.5	280	270	150	138	172	3-M5	4.5
	M150	1.5	290	280	156	144	177	3-M5	4.5
	M155	1.5	300	290	162	150	182	3-M5	4.5
	M160	1.5	310	300	168	156	187	3-M5	4.5
	M165	1.5	320	310	174	162	192	3-M5	4.5
	M170	1.5	330	320	180	168	197	3-M5	4.5
	M175	1.5	340	330	186	174	202	3-M5	4.5
	M180	1.5	350	340	192	180	207	3-M5	4.5
	M185	1.5	360	350	198	186	212	3-M5	4.5
	M190	1.5	370	360	204	192	217	3-M5	4.5
	M200	1.5	380	370	210	198	222	3-M5	4.5
	M210	1.5	390	380	216	204	227	3-M5	4.5
	M220	1.5	400	390	222	210	232	3-M5	4.5
	M230	1.5	410	400	228	216	237	3-M5	4.5
	M240	1.5	420	410	234	222	242	3-M5	4.5
	M245	1.5	430	420	240	228	247	3-M5	4.5
	M260	1.5	440	430	246	234	252	3-M5	4.5
	M260	1.5	450	440	252	240	257	3-M5	4.5
	M275	1.5	460	450	258	246	262	3-M5	4.5
	M280	1.5	470	460	264	252	267	3-M5	4.5
	M300	1.5	480	470	270	258	272	3-M5	4.5
	M440	1.5	520	510	294	282	309	3-M5	4.5
	M460	1.5	540	530	306	294	314	3-M5	4.5

垫圈
螺母
吊环
30



请按图示订货

■ GYAK11-M10-0.5

型号

代码

M

螺距

GYAK02

M6*

0.5

交期Delivery

3天 发货

○不含周日