


防松动型螺母 ◀ 径向锁紧型 圆形



代码	类型		形状	精度	端面偏摆	材质		热处理	表面处理
						国标	相当		
GYAL01	经济型	径向锁紧型	三槽	6H	0.002~0.005	45	S45C	28~32HRC	发黑

- 锁紧螺母的锁紧方向为两点或三点式径向锁定, 适用于设计或装配上受限, 无法使用其他产品的情况
- 由于热处理工艺表面可能会出现少许发红



型号		螺距	A	H	g	t	d	n·m	扭紧力矩 (NM)		
代码	公称尺寸										
GYAL01	M6	0.75	16	8	3	1.6	12	3-M4	3.5		
		1.0									
	M8	0.75					13				
		1.0									
	M9	0.75	15								
	M10	1.0	16								
	M12	1.0									
		1.25	21								
	M14	1.0	25								
		1.25									
	M15	1.0									
		1.5									
	M16	1.0	28	10	4	2	23	3-M5	4.5		
		1.5									
	M17	1.0					25				
		1.5	30								
	M18	1.0	32			2.5	27			3-M6	8
		1.5	35				30				
	M24		38				33				
	M25		45				40				
	M30		52	46	3	3-M8	18				
	M32		58	52							
	M35		65	59							
	M40										
	M44										
	M45										
	M50	1.5	70	14	6			3	64	3-M8	18
		2.0									
	M52	1.5									
	M54										
	M55	1.5	75	16	7	3	69	3-M8	18		
		2.0									
M58	1.5	76									
		80									
M60		85	18	8	3.5	73	3-M8			18	
M65		92				78					
M70		98				84					
M75		105				90					
M80						96					



请按图示订货

GYAL01-M6-0.75

型号		螺距
代码	M	
GYAL01	M6	0.75
		1.0



交期Delivery

3天

发货

○ 本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台