




轴用挡圈 ◀ E型 弹簧钢/不锈钢 日标



代码	类型	材质	硬度	表面处理	适用标准
YCS11	E型轴用挡圈	弹簧钢	42~51HRC	磷化黑	JIS B 2805-1978
YCS12		SUS420-J2	34~42HR	/	



型号		挡圈								适用轴（参考）						
代码	规格	d		D		H		t		d ₁ 的分类		d ₂		m		n(min)
										大于	以下					
YCS11 YCS12	1.2	1.2	0.09	3	±0.1	1	0.25	0.3	±0.025	1.4	2	1.23	+ _{0.06} ₀	0.4	+ _{0.05} ₀	0.6
	1.5	1.5		4	1.3	2		2.5	1.53	0.8						
	2	2		5	1.7	2.5		3.2	2.05	1						
	2.5	2.5		6	2.1	3.2		4	2.55	1						
	3	3	0.12	7	2.6	0.35	0.6	±0.04	4	5	3.05	+ _{0.075} ₀	0.7	+ _{0.1} ₀	1	
	4	4		9	3.5				5	7	4.05				1.2	
	5	5		11	4.3				6	8	5.05				1.2	
	6	6		12	5.2				7	9	6.05				1.2	
	7	7	0.15	14	6.1	0.35	0.8	±0.04	8	11	7.1	+ _{0.09} ₀	0.9		1.5	
	8	8		16	6.9				9	12	8.1				1.8	
	9	9		18	7.8				10	13	9.1				2.1	



请按图示订货

■YCS11-1.2

型号

代码规格

YCS111.2



交期Delivery

3天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台