




轴用挡圈 ◀ C型 弹簧钢/不锈钢 国标



代码	类型	材质	表面处理	适用标准
YCS21	C型轴用挡圈	65Mn(弹簧钢)	发黑	GB/T 894.1-1986
YCS22		SUS304		

规格8(不含8)以下如图所示 d_4 :将挡圈嵌入 d_1 时的最大外周直径(间隙外径)



垫圈
吊环母
30

型号		挡圈							安装沟槽尺寸					孔							
代码	规格	d ₁ 轴径	d ₃		t		b≈	d0	a	d ₂		m		n≥	d ₄ ≥						
			基本尺寸	极限偏差	基本尺寸	极限偏差				基本尺寸	极限偏差	基本尺寸	极限偏差								
YCS21 YCS22	3*	3	2.7	+0.04 -0.15	0.4	+0.03 -0.06	0.8	1	0.95	2.8	0 -0.04	0.5	+0.14 0	0.3	7.2						
	4*	4	3.7				0.88		1.1	3.8	0				8.8						
	5*	5	4.7				1.12		1.25	4.8	-0.048				10.7						
	7*	7	6.5				+0.06 -0.18		1.32	1.2	1.55				6.7	0 -0.058	0.5	13.8			
	10	10	9.3	+0.10 -0.36	1	+0.05 -0.13	1.44	1.5		9.6	0 -0.11	1.1		0.6	17.6						
	11*	11	10.2				1.52			10.5				0.8	18.6						
	12	12	11				1.72			11.5				0.9	19.6						
	13	13	11.9				1.88			12.4				20.8							
	14	14	12.9				2.0			13.4				22							
	15	15	13.8				2.32			14.3				1.1	23.2						
	16	16	14.7				2.48			15.2				1.2	24.4						
	17	17	15.7				2.48			16.2				1.5	25.6						
	18	18	16.5				2.48			17				1.5	27						
	19	19	17.5				+0.13 -0.42								2.68	2		18	0 -0.13		1.5
	20	20	18.5	19	29																
	21*	21	19.5	20	31																
	22	22	20.5	21	32																
	24	24	22.2	+0.21 -0.42	1.2		3.32			22.9	0 -0.21	1.3		1.7	34						
	25	25	23.2				3.6			23.9					35						
	28	28	25.9				3.72			26.6					2.1	38.4					
	29*	29	26.9				3.92			27.6					39.8						
	30	30	27.9	+0.25 -0.50	1.5	+0.06 -0.15	4.32	2.5	/	28.6	0 -0.25	1.7		2.6	42						
	32	32	29.6				4.32			30.3					2.6	44					
	34*	34	31.5				4.52			32.3					2.6	46					
	35	35	32.2				4.52			33					2.6	48					
	36	36	33.2				5.0			34					3	49					
	37	37	34.2				5.0			35					50						
	38	38	35.2				5.0			36					51						
	40	40	36.5				5.0			37.5					53						
	45	45	41.5				5.0			42.5					56						
	48	48	44.5				5.0			45.5					62.8						
	50	50	45.8	+0.39 -0.90			5.48			47	0 -0.25	2.2			64.8						
	52*	52	47.8				49			67											
	55*	55	50.8				52			70.4											
	58*	58	53.8				55			73.6											
	60	60	55.8	+0.46 -1.10	2	+0.06 -0.18	6.12			57	0 -0.30	2.7		4.5	75.8						
	75*	75	70.5				6.32			72					92.8						
	78*	78	73.5				6.32			75					96.2						
	80*	80	74.5				7			76.5					98.2						
	82*	82	76.5				7			78.5					101						
	85*	85	79.5				7			81.5					104						
	90*	90	84.5	+0.54 -1.30	2.5	+0.07 -0.22	7.6			86.5	0 -0.35			5.3	110						
	95*	95	89.5				9.2			91.5					115						
	100*	100	94.5				9.2			96.5					121						
	105*	105	98				10.7			101					132						

带*尺寸不适用于YCS22



请按图示订货

■YCS21-3

型号

代码

规格

YCS21

3



交期Delivery

3天

发货

○本产品发货时间不含周日