


定位珠 ◀ 长型・金属球头/树脂球头



代码	类型		载荷	主体			球头		弹簧	
				材质	硬度	表面处理	材质	硬度	材质	
YZH01	长型	金属球头	超轻载	S45C	30-35HRC	发黑	SUJ2	56HRC-	SWP-B	
YZH02			轻载							
YZH03			重载							
YZH04			超重载	SUS304	/	/				
YZH11	长型	树脂球头	超轻载	S45C	30-35HRC	电镀	聚缩醛	/	SWP-B	
YZH12			轻载							
YZH13			重载							
YZH14			超重载							电镀

30



■长型·金属球头

型号		d	L	H	h	E	负载 (N)								
代码	M						超轻载		轻载		重载		超重载		
							min.	max.	min.	max.	min.	max.	min.	max.	
YZH01	3	1.5	13	0.5	1	1.5	0.29	0.66	0.9	2.1	1.49	3	2.1	4.9	
	4	2.5	15		1.5	2	0.59	1.61	1.9	5	3.8	5.1	2.4	12.5	
	5	3	18	0.8	2	2.5	0.9	3.22	2.8	9.9	4.8	19.7	11.6	25	
	6		20		3	1.5	4.8	14.8	9.7	29.5	18.6	35.2			
YZH02	8	4	23	1	2.5	4	2.3	6.46	6.8	19.7	12.6	39.3	24.4	46.7	
YZH03	10	5	27	1.2		5	2.9	8.2	8.7	24.6	18.5	49.1	26.6	58.6	
YZH04	12	7.1	32	1.8		3	6	3.4	9.78	9.7	29	19.5	58.9	26	62.2
	16	9.5	40	2.5			8	5.6	15.9	15.6	49.1	29.3	98.1	55.3	115.9

① M3/M4前端部无扳手槽，仅为内六角孔安装 / ② 负载min.表示初始负载，max.表示球头最大压入限度时的负载。

■长型·树脂球头

型号		d	H	L	h	E	负载 (N)							
代码	M						超轻载		轻载		重载		超重载	
							min.	max.	min.	max.	min.	max.	min.	max.
YZH11 YZH12 YZH13 YZH14	4	2.5	0.7	15	1.5	2	0.59	1.61	1.9	5	3.8	5.1	2.4	12.5
	5	3	0.8	18	2	2.5	0.9	3.22	2.8	9.9	4.8	19.7	11.6	25
	6	4	1	20	2.5	3	1.5	4.95	4.8	14.8	9.7	29.5	18.6	35.2
	23			2.5	4	2.3	6.46	6.8	19.7	12.6	39.3	24.4	46.7	
	10	5	1.2	27	3	5	2.9	8.2	8.7	24.6	18.5	49.1	26.6	58.6
	12	7.1	1.8	32		6	3.4	9.78	9.7	29	19.5	58.9	26	62.2
	16	9.5	2.5	40		8	5.6	15.9	15.6	49.1	29.3	98.1	55.3	115.9



型号

型号

代码

M

YZH01

3



3

发货

○本产品发货时间不含周日