



# 定位柱 ◀ 长行程不锈钢型



| 代码    | 类型          | 载荷  | 主体<br>材质 | 销<br>材质 | 硬度    | 使用环境<br>温度 |
|-------|-------------|-----|----------|---------|-------|------------|
| YZP11 | 长行程<br>不锈钢型 | 超轻载 | SUS304   | SUS440C | 55HRC | -30~150°C  |
| YZP12 |             | 轻载  |          |         |       |            |
| YZP13 |             | 重载  |          |         |       |            |
| YZP14 |             | 超重载 |          | 聚缩醛     | /     | -30~80°C   |
| YZP15 |             | 超轻载 |          |         |       |            |
| YZP16 |             | 轻载  |          |         |       |            |
| YZP17 | 树脂<br>球头    | 重载  |          |         |       |            |
| YZP18 |             | 超重载 |          |         |       |            |

① 未进行防松动处理；

② 负载min.表示初始负载，max.表示凸销最大压入限度时的负载。



| 型号                                       |                                          | H   | d   | L   | L1 | E   | 负载(N) |      |      |      |      |      |      |      |      |
|------------------------------------------|------------------------------------------|-----|-----|-----|----|-----|-------|------|------|------|------|------|------|------|------|
| 代码                                       | M                                        |     |     |     |    |     | 超轻载   |      | 轻载   |      | 重载   |      | 超重载  |      |      |
|                                          |                                          |     |     |     |    |     | min.  | max. | min. | max. | min. | max. | min. | max. |      |
| 金属球头<br>YZP11<br>YZP12<br>YZP13<br>YZP14 | 3                                        | 1.5 | 1   | 15  | 15 | 0.9 | 0.11  | 0.5  | 0.4  | 1.3  | 0.8  | 2.94 | 1.1  | 3.42 |      |
|                                          |                                          | 3   |     |     |    |     | 0.11  | 0.5  | 0.2  | 1.3  | 0.6  | 2.93 | 0.8  | 3.41 |      |
|                                          | 4                                        | 2   | 1.6 | 24  | 24 | 1.3 | 0.26  | 0.75 | 0.9  | 2    | 2    | 8.8  | 6.1  | 13.8 |      |
|                                          |                                          | 4   |     |     |    |     | 0.17  | 0.75 | 0.6  | 2.1  | 1.9  | 8.75 | 5.8  | 13.6 |      |
|                                          | 5                                        | 3   | 2   | 20  | 20 | 1.5 | 0.39  | 3.1  | 1.4  | 9.7  | 2.7  | 16.3 | 6.8  | 22   |      |
|                                          |                                          | 5   |     |     |    |     | 0.34  | 3.1  | 1.1  | 10.3 | 1    | 17.1 | 5.7  | 21.5 |      |
|                                          | 6                                        | 3   | 2.5 | 25  | 25 | 2   | 1.79  | 3.15 | 6    | 9.8  | 8    | 26.4 | 15.8 | 35.6 |      |
|                                          |                                          | 5   |     |     |    |     | 1.49  | 3.15 | 3.4  | 9.86 | 4.4  | 26.6 | 12.9 | 34.4 |      |
|                                          | 树脂球头<br>YZP15<br>YZP16<br>YZP17<br>YZP18 | 8   | 3   | 3.1 | 25 | 25  | 2.5   | 1.89 | 3.25 | 6    | 9.9  | 14.7 | 27   | 21.9 | 36.3 |
|                                          |                                          |     | 5   |     |    |     |       | 1.39 | 3.25 | 4    | 9.83 | 6.7  | 26.6 | 14.7 | 34.5 |
| 10                                       |                                          | 5   | 3.8 | 30  | 30 | 3   | 1.59  | 4.7  | 5.7  | 14.7 | 8.2  | 45.7 | 24.5 | 58.6 |      |
|                                          |                                          | 10  |     |     |    |     | 1.59  | 4.7  | 4.4  | 14.7 | 6.2  | 45.1 | 19.5 | 58.7 |      |
| 12                                       |                                          | 5   | 5.5 | 30  | 30 | 4   | 1.69  | 4.8  | 5.8  | 14.7 | 18.2 | 49   | 34.9 | 63.6 |      |
|                                          |                                          | 15  |     |     |    |     | 1.59  | 4.8  | 5    | 14.7 | 8.2  | 49.1 | 25.5 | 63.6 |      |
|                                          |                                          | 10  |     |     |    |     | 1.79  | 4.8  | 6.9  | 14.7 | 7.5  | 48.9 | 20.1 | 63.7 |      |
| 16                                       |                                          | 10  | 8   | 57  | 57 | 5   | 2.79  | 10.9 | 9.2  | 34.2 | 18.9 | 68.5 | 38.7 | 88.4 |      |
|                                          |                                          | 15  |     |     |    |     | 2.59  | 10.9 | 8.6  | 34.4 | 14.4 | 68.6 | 33.9 | 88.1 |      |
|                                          |                                          | 20  |     |     |    |     | 1.99  | 11.1 | 7.1  | 34.4 | 4.2  | 68.6 | 25.4 | 88.1 |      |



请按图示订货

## YZP11-M3-H1.5

| 型号    |   |       |
|-------|---|-------|
| 代码    | M | H     |
| YZP11 | 3 | 1.5 3 |



交期Delivery

5天

发货

○本产品发货时间不含周日