


压缩弹簧 ◀ 外径基准型(不锈钢)



代码	类型	材质		允许位移量	弹簧常数公差
		国标	相当		
AUBB	外径基准型(不锈钢)	0Cr18Ni9	SUS304 WP8	$L \times (15 \sim 25) \%$	$\pm 10 \%$

■ 外径D公差: $\phi 10$ 以下-0.5mm~0mm $\phi 12$ 以上-0.8mm~0mm
■ 长度L公差: 50以下 ± 1.5 , 55以上 ± 2.5
压紧长度为参考值, 因批次不同会有偏差
理论使用次数100万次
AUBB-D4-L5 两端均未进行磨削加工。

型号		d	压紧长度	Fmax	N(kgf) max	
代码	D					
AUBB	4	(5)	0.55	3.3	1.25	6.1
		10	0.65	7	2.5	12.3
		15	0.7	10.3	3.75	18.4
		20	0.75	14.4	5	24.5
		25	0.8	19.4	5	24.5
	5	5	0.6	2.9	1.25	6.1
		10	0.75	6.9	2.5	12.3
		15	0.8	9.8	3.75	18.4
		20	0.85	13.4	5	24.5
		25	0.9	17.6	6.25	30.6
	6	30	0.9	21.8	7.5	36.8
		5	0.8	3.6	1.25	12.3
		10	0.9	6.8	2.5	24.5
		15	1	10.5	3.75	36.8
		20	1.1	14.6	5	49
		25	1.1	17.9	6.25	61.3
		30	1.2	23.1	6	58.8
		35	1.2	27.3	7	68.6
		40	1.2	31.2	8	78.5
		45	1.3	34.8	9	88.3
		50	1.3	38.4	10	98.1
		60	1.3	44.2	9	88.3
	8	70	1.4	58.5	10.5	103
		10	1.1	6.9	2.5	24.5
		15	1.2	9.9	3.75	36.8
		20	1.3	14	5	49
		25	1.3	14.5	6.25	61.3
		30	1.4	21.4	7.5	73.5
		35	1.4	22	8.75	85.8
		40	1.5	28.9	10	98.1
	10	45	1.5	32.6	11.25	110
		10	1.3	7.2	2.5	24.5
		15	1.4	10.2	3.75	36.8
		20	1.5	13.99	5	49
		25	1.5	16.1	6.25	61.3
		30	1.6	20.4	7.5	73.5
		35	1.6	22.8	8.75	85.8
		40	1.7	27.2	10	98.1
		45	1.7	30.6	11.25	110
		50	1.8	36.5	12.5	123
		60	1.8	41.4	15	147
		70	1.9	50.8	17.5	172

型号		d	压紧长度	Fmax	N(kgf) max	
代码	D					L
AUBB	12	15	1.5	9.4	3.75	36.8
		20	1.6	12.4	5	49
		25	1.7	16.2	6.25	61.3
		30	1.8	20.3	7.5	73.5
		40	1.9	28	10	98.1
		50	2	35.5	12.5	123
		60	2.1	43.6	15	147
		70	2.1	48.8	17.5	172
	13	80	2.2	58.5	20	196
		15	1.8	9.5	3.75	73.5
		20	1.9	12.9	5	98.1
		25	2	17	6.25	123
		30	2.1	20.5	7.5	147
		40	2.3	28	10	196
		45	2.3	32.2	11.25	221
		50	2.4	36	12.5	245
	14	60	2.5	44.4	12	235
		70	2.6	54	14	275
		15	1.9	10	3.75	73.5
		20	2	13.5	5	98.1
		25	2.1	16.3	6.25	123
		30	2.3	21.3	7.5	147
		35	2.3	24.7	8.75	172
		40	2.4	28.2	10	196
	16	60	2.6	43.6	15	294
		80	2.7	61.4	16	314
		15	2	10	3.75	73.5
		20	2.1	12.1	5	98.1
		25	2.3	17.3	6.25	123
		30	2.4	21	7.5	147
		35	2.5	24.4	8.75	172
		40	2.6	28	10	196
	20	45	2.7	31.7	11.25	221
		50	2.7	35.8	12.5	245
		60	2.9	43.5	15	294
		70	2.9	49.4	17.5	343
		80	3	59.3	16	314
		25	2.9	16.7	6.25	184
		30	3	20.3	7.5	221
		35	3	22.7	8.75	257
		40	3.2	27.2	10	294
		45	3.2	29.6	9	265
		50	3.4	38.3	10	294
		60	3.5	44.6	12	353

■ AUBB: Fmax(容许位移量) = $L \times (15 \sim 25) \%$



请按图示订货

■ AUBB-D4-L10

型号

代码	D	L
AUBB	4	5 10



交期Delivery

5天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌, 让采购更便捷, 让设计更高效!

弹簧 / 氮气弹簧 33