




轴用挡圈 ◀ C型 弹簧钢/不锈钢 国标



代码	类型	材质	表面处理	适用标准
YCS21	C型轴用挡圈	65Mn(弹簧钢)	发黑	GB/T 894.1-1986
YCS22		SUS304		

规格5以下如图所示

d₄:将挡圈嵌入d₁时的最大外周直径(间隙外径)



型号		挡圈							安装沟槽尺寸					孔	
代码	规格	d ₁ 轴径	d ₃		t		b≈	d ₀	a	d ₂		m		n≥	d ₄ ≥
			基本尺寸	极限偏差	基本尺寸	极限偏差				基本尺寸	极限偏差				
YCS21 YCS22	3*	3	2.7		0.4	+0.03 -0.06	0.8		0.95	2.8	0 -0.04	0.5			7.2
	4*	4	3.7	+0.04 -0.015			0.88	1	1.1	3.8	0 -0.048		0.3		8.8
	5*	5	4.7		0.6	+0.04 -0.07	1.12		1.25	4.8	0 -0.048	0.7			10.7
	7*	7	6.5	+0.06 -0.018			1.32	1.2	1.55	6.7	0 -0.058			0.5	13.8
	10	10	9.3				1.44			9.6				0.6	17.6
	11*	11	10.2				1.52	1.5		10.5				0.8	18.6
	12	12	11				1.72			11.5					19.6
	13	13	11.9				1.88			12.4				0.9	20.8
	14	14	12.9				2.0			13.4	0 -0.11	1.1		1.1	22
	15	15	13.8	+0.10 -0.36	1		2.32	1.7		14.3				1.2	23.2
	16	16	14.7				2.48			15.2				1.2	24.4
	17	17	15.7				2.48			16.2				1.5	25.6
	18	18	16.5				2.48			17					27
	19	19	17.5				2.48			18					28
	20	20	18.5				2.68			19	0 -0.13			1.5	29
	21*	21	19.5	+0.13 -0.42						20					31
	22	22	20.5							21					32
	24	24	22.2				3.32	2		22.9				1.7	34
	25	25	23.2				3.6			23.9	0 -0.21	1.3			35
	28	28	25.9	+0.21 -0.42	1.2		3.72			26.6				2.1	38.4
	29*	29	26.9				3.92			27.6					39.8
	30	30	27.9				4.32			28.6					42
	32	32	29.6				4.32			30.3				2.6	44
	34*	34	31.5				4.52	2.5		32.3				2.6	46
	35	35	32.2	+0.25 -0.50			4.52			33					48
	36	36	33.2				5.0			34	0 -0.25	1.7		3	49
	37	37	34.2		1.5	+0.06 -0.15				35					50
	38	38	35.2							36					51
	40	40	36.5							37.5					53
	45	45	41.5							42.5				3.8	56
	48	48	44.5	+0.39 -0.90						45.5					62.8
	50	50	45.8							47					64.8
	52*	52	47.8				5.48			49					67
	55*	55	50.8		2	+0.06 -0.18	6.12			52		2.2		4.5	70.4
	58*	58	53.8							55					73.6
	60	60	55.8							57					75.8
	75*	75	70.5	+0.46 -1.10			6.32	3		72	0 -0.30				92.8
	78*	78	73.5							75					96.2
	80*	80	74.5							76.5					98.2
	82*	82	76.5				7			78.5					101
	85*	85	79.5		2.5	+0.07 -0.22				81.5	0 -0.35	2.7		5.3	104
	90*	90	84.5				7.6			86.5					110
	95*	95	89.5	+0.54 -1.30			9.2			91.5					115
	100*	100	94.5							96.5	0 -0.54	3.2	+0.18 0	6	121
	105*	105	98		3		10.7	4		101					132

带*尺寸不适用于YCS22



请按图示订货

■YCS21-3

型号

代码

规格

YCS21

3



交期Delivery

3天

发货

○本产品发货时间不含周日

垫圈
吊环
螺母

34