




孔用挡圈 ◀ C型 弹簧钢/不锈钢 国标



d_4 : 将挡圈嵌入 d_1 时的最小内周直径(间隙内径)。

代码	类型	材质	表面处理	适用标准
YCS41	C型孔用挡圈	65Mn (弹簧钢)	发黑	GB/T 893.1-1986
YCS42		SUS304	/	

型号		公称规格 d ₁	挡圈						安装沟槽尺寸				其它		
代码	规格		d ₃		t		b≈	d ₀	d ₂		m			n≥	d ₄ ≤
			基本尺寸	极限偏差	基本尺寸	极限偏差			基本尺寸	极限偏差	基本尺寸	极限偏差			
弹簧钢 YCS41 SUS304 YCS42	9*	9	9.8	+0.36 -0.10	0.6	+0.04 -0.07	1.2	1.0	9.4	+0.09 0	0.7	+0.14 0	0.6	2	
	10	10	10.8		0.8	+0.04 -0.10	1.7	1.5	10.4	+0.11 0	0.9		3		
	11	11	11.8						11.4				4		
	12	12	13						12.5				5		
	13	13	14.1						13.6				+0.13 0	1.1	6
	14	14	15.1		14.6	7									
	15	15	16.2		15.7	8									
	16	16	17.3		16.8	9									
	17	17	18.3	+0.42 -0.13	1.0	+0.05 -0.13	2.1	17.8	+0.21 0	1.3	10				
	18	18	19.5					19.0			11				
	19	19	20.5					20.0			12				
	20	20	21.5					21.0			13				
	21*	21	22.5				2.5	2.0	22.0	+0.25 0	1.7		14		
	22	22	23.5						23.0				15		
	24	24	25.9						25.2				16		
	25	25	26.9						26.2				17		
	26	26	27.9	2.8	3.2	27.2	+0.30 0	2.2	18						
	28	28	30.1			29.4			19						
	30	30	32.1			31.4			20						
	31*	31	33.4			32.7			21						
	32	32	34.4	+0.50 -0.25	1.2	+0.06 -0.15	4.0	33.7	+0.35 0	2.7	22				
	34*	34	36.5					35.7			23				
	35	35	37.8					37.0			24				
	36*	36	38.8					38.0			25				
	37*	37	39.8				4.7	3.0	39.0	+0.30 0	2.2		26		
	38	38	40.8						40.0				27		
	40	40	43.5						42.5				28		
	42	42	45.5						44.5				29		
	45	45	48.5	4.7	3.0	47.5	+0.30 0	2.2	30						
	47*	47	50.5			49.5			31						
	48*	48	51.5			50.5			32						
	50	50	54.2			53.0			33						
	52	52	56.2	+1.10 -0.46	2	+0.06 -0.18	5.2	55.0	+0.35 0	2.7	34				
	55*	55	59.2					58.0			35				
	56*	56	60.2					59.0			36				
	58*	58	62.2					61.0			37				
	60	60	64.2				5.7	3.0	63.0	+0.35 0	2.7		38		
	62	62	66.2						65.0				39		
	63*	63	67.2						66.0				40		
	65*	65	69.2						68.0				41		
68*	68	72.5	+0.07 -0.22	2.5	+0.07 -0.22	6.3	71.0	+0.35 0	2.7	42					
70	70	74.5					73.0			43					
72*	72	76.5					75.0			44					
75*	75	79.5					78.0			45					
78*	78	82.5				6.8	3.0	81.0	+0.35 0	2.7	46				
80*	80	85.5						83.5			47				
85*	85	90.5						88.5			48				
88*	88	93.5						91.5			49				
90*	90	95.5	+1.30 -0.54	2.5	+0.07 -0.22	7.3	93.5	+0.35 0	2.7	50					
95*	95	100.5					98.5			51					

带*尺寸不适用于YCS42

■ YCS41-9



请按图示订货

型号	
代码	规格
YCS41	9



交期Delivery

3天

发货

○ 本产品发货时间不含周日