




磁铁 ◀ 圆形.轴向磁力型



代码	类型	磁力方向	材质	表面处理	耐热温度
YLS01	圆型	轴向	钕磁铁	镀镍	80°C
YLS02			强力钕磁铁		60°C
YLS03			耐热钕磁铁		150°C
YLS04			钴磁铁	/	200°C
YLS11			钕磁铁	环氧树脂涂层	80°C

磁力方向：轴向



型号		L	吸引力N(kgf)			表面磁通密度高斯(G)		
代码	D		YLS01/03	YLS02	YLS04	YLS01/03	YLS02	YLS04
YLS01 YLS02 YLS03 YLS04	1	2	0.05(0.005)	0.08(0.008)	/	1000-1300	1900-2100	/
		3	0.06(0.006)	/	/	1100-1400	/	/
		5	0.07(0.007)	0.10(0.010)	/	1200-1500	2100-2300	/
	2	2	0.55(0.055)	0.77(0.08)	0.39(0.04)	2300-2600	3500-3700	2000-2200
		3	0.65(0.065)	0.90(0.09)	0.49(0.05)	3000-3300	3700-3900	2600-2800
		4	0.70(0.07)	0.93(0.09)	/	3200-3600	3700-3900	/
	3	5	0.75(0.075)	1.01(0.10)	0.49(0.05)	3000-3300	4100-4300	2600-2800
		1	1.05(0.105)	1.39(0.14)	/	1900-2400	2700-2900	/
		2	1.55(0.155)	2.05(0.21)	1.08(0.11)	3000-3300	3700-4000	2600-2800
	4	3	1.95(0.195)	2.55(0.26)	1.37(0.14)	3200-3500	4200-4500	2800-3000
		4	2.20(0.22)	2.93(0.30)	1.47(0.15)	3300-3600	4400-4700	2900-3100
		5	2.30(0.23)	3.06(0.31)	1.57(0.16)	3400-3700	4500-4800	2900-3100
	5	6	2.80(0.28)	3.60(0.37)	/	4000-4300	4600-4800	/
		1	1.45(0.145)	/	/	1900-2200	/	/
		2	2.80(0.28)	3.69(0.38)	1.86(0.19)	3000-3300	4100-4300	2600-2800
	6	3	3.80(0.38)	4.97(0.51)	2.55(0.26)	3500-3800	4200-4500	3100-3300
		4	4.30(0.43)	5.60(0.57)	2.93(0.30)	3700-4000	4500-4800	3200-3400
		5	4.65(0.465)	6.11(0.62)	3.14(0.32)	3900-4200	4800-5100	3300-3600
	7	8	6.80(0.68)	8.50(0.87)	/	4200-4700	5100-5400	/
		10	6.95(0.70)	9.05(0.92)	/	4200-4700	5200-5500	/
	8	1	1.43(0.143)	/	/	1700-2000	/	/
		2	3.90(0.39)	5.10(0.52)	2.65(0.27)	2900-3200	3500-3700	2500-2700
		3	5.75(0.575)	7.51(0.77)	3.82(0.39)	3700-4000	4200-4500	3200-3400
	9	4	6.85(0.685)	8.92(0.91)	4.61(0.47)	3900-4200	4600-4900	3400-3600
		5	7.60(0.76)	9.93(1.01)	5.12(0.52)	4200-4500	4900-5100	3500-3800
		6	8.10(0.81)	10.57(1.08)	5.39(0.55)	4200-4500	5100-5400	3600-3800
	10	8	8.95(0.90)	11.64(1.19)	/	4500-4900	5200-5500	/
		10	9.80(1.00)	12.77(1.30)	/	4700-5000	5400-5700	/
	11	2	4.95(0.5)	6.50(0.66)	3.33(0.34)	2800-3100	3100-3400	2400-2600
		3	7.60(0.76)	9.93(1.01)	5.10(0.52)	3600-3900	4000-4300	3100-3300
		4	9.60(0.96)	12.48(1.27)	6.46(0.66)	3800-4100	4600-4900	3300-3500
	12	5	10.85(1.85)	/	7.25(0.74)	4200-4500	/	3600-3800
		6	11.75(1.75)	15.29(1.56)	7.84(0.80)	4300-4600	5100-5400	3700-3900
		8	11.80(1.28)	15.34(1.66)	/	4500-4900	5400-5600	/
	13	10	11.80(1.18)	15.39(1.69)	/	4700-5000	5500-5800	/
		2	6.65(0.665)	/	4.41(0.45)	2300-2600	/	2000-2200
		3	10.75(1.075)	14.01(1.43)	7.45(0.76)	3100-3400	3500-3800	2700-2900
	14	5	17.90(1.79)	23.33(2.38)	11.96(1.22)	4100-4400	4700-5000	3500-3700
		6	20.59(2.10)	26.76(2.73)	/	4700-4900	5100-5400	/
		8	23(2.3)	29.94(3.06)	15.39(1.57)	4500-4800	5400-5700	3900-4100
	15	10	24(2.4)	31.23(3.19)	/	4900-5200	5600-5900	/
		2	24(2.4)	/	5.29(0.54)	1900-2200	/	1700-1900
		3	14.10(1.41)	18.34(1.87)	9.41(0.96)	2700-3000	3100-3400	2400-2600
	16	5	24.75(2.475)	32.23(3.29)	16.56(1.69)	3700-4000	4300-4600	3200-3400
		8	34(3.4)	/	23.03(2.35)	4600-4900	/	4000-4200
		10	38(3.8)	49.43(5.04)	25.48(2.60)	4800-5100	5500-5800	4100-4300
	17	2	9(0.9)	/	5.98(0.61)	1500-1800	/	1250-1500
		3	16.45(1.645)	/	11.08(1.13)	2400-2700	/	2100-2300
		5	31.15(3.115)	/	20.87(2.13)	3500-3800	/	3000-3200
	18	8	46.50(4.65)	/	31.07(3.17)	4400-4700	/	3800-4000
		10	52.70(5.27)	/	35.28(3.60)	4700-5000	/	4000-4200
	19	2	10.55(1.055)	/	7.04(0.72)	1300-1600	/	1100-1300
		3	19.55(1.955)	/	13.13(1.34)	2200-2500	/	1950-2100
		5	39.55(4.03)	/	26.46(2.70)	3000-3300	/	2600-2800
	20	8	64.35(6.46)	/	43.02(4.39)	4100-4400	/	3500-3700
		10	75.85(7.74)	/	50.67(5.17)	4500-4800	/	3800-4000
		3	34.32(3.50)	/	/	1600-1900	/	/
		10	98.06(10.00)	/	/	4100-4400	/	/

小
零
件

36

型号		L	吸引力N(kgf)	表面磁通密度高斯(G)
代码	D			
YLS11	3	5	2.3(0.24)	4000-4200
	4	5	4.4(0.45)	4200-4400
	5	6	6.8(0.7)	4400-4600
	6	6	9.8(1.0)	4400-4600
	8	8	18.6(1.9)	4600-4800
	10	10	33.4(3.4)	4800-5000

注：① 利用树脂涂层提高了耐水性能和防锈效果；
② 吸引力,表面磁通密度是指磁铁单价的值.(仅供参考)



请按图示订货

■ YLS01-D1-L2

型号		
代码	D	L
YLS01	1	2



交期Delivery

3 天 发货

○ 本产品发货时间不含周日

P1482