





经济型膜片式联轴器 ◀ 螺钉夹紧型 单膜片/双膜片



单膜片DCDE03



双膜片DCDE13



代码	类型	材质		附件
		主体	膜片	
DCDE03	螺钉夹紧型	不锈钢	单膜片	内六角圆柱头螺钉
DCDE13			双膜片	

特点:

- 1.高扭矩,高刚性;
- 2.零回转间隙;
- 3.顺时针和逆时针回转时特性完全一样;
- 4.不锈钢膜片能补偿径向、角向、轴向偏差;
- 5.采用摩擦结合进行传递、无间隙、最适合超精密控制。

型号	h-p														
代码	D														
19	h	3			4			5			6			6.35	
	p	3	4	5	6	6.35	7	8	4	5	6	6.35	7	8	8
26	h	4			5			6			6.35			7	
	p	4	5	6	6.35	7	8	9	9.525	10	11	12	12.7	13	14
29	h	5			6			6.35			7			8	
	p	5	6	6.35	7	8	9	9.525	10	11	12	12.7	13	14	15
34	h	5			6			6.35			7			8	
	p	5	6	6.35	7	8	9	9.525	10	11	12	12.7	13	14	15
39	h	8			9			9.525			10			11	
	p	8	9	9.525	10	11	12	12.7	13	14	15	16	17	18	19
44	h	8			9			9.525			10			11	
	p	8	9	9.525	10	11	12	12.7	13	14	15	16	17	18	19
56	h	12			12.7			13			14			15	
	p	12	12.7	13	14	15	16	17	18	19	20	21	22	23	24
68	h	14			15			16			18			19	
	p	14	15	16	17	18	19	20	21	22	23	24	25	26	27
82	h	24			25			25.4			26			28	
	p	24	25	25.4	26	27	28	29	30	31	32	33	34	35	36

联轴器

06



www.vipdo.cn 400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌,让采购更便捷,让设计更高效!

经济型膜片式联轴器 ◀ 螺钉夹紧型 单膜片/双膜片

型号		L	A	C	Q	U	M	锁紧 扭矩 (N.m)	额定 扭矩 (N.m)	最大 扭矩 (N.m)	最高 转速 (r/min)	惯性 力矩 (kg.m ²)	静态扭 转刚性 (N.m/rad)	容许安装偏差			重量 (g)
代码	D													径向 (mm)	角向(°)	轴向 (mm)	
单膜片 DCDE03	19	19.25	3.1	9	—	1.25	M3	1	0.8	1.6	10000	1.4×10 ⁻⁶	580	0.02	1	±0.10	26
	26	23.5	3.3	10.5		2.5			1.5	3		6.1×10 ⁻⁶	950			±0.15	61
	29	26.5	3.75	12		M4	1.5	3	6	1.0×10 ⁻⁵		1350	0.15	2	±0.30	82	
	34	27.35	4	3.35				M4	4	8		2.0×10 ⁻⁵	2000	±0.20	117		
	39	34.35	5	15		4.35	M4	3.4	6	12		4.3×10 ⁻⁵	4500	0.02	1	±0.25	195
	44	34.6				4.6			10	20		7.0×10 ⁻⁵	5200			±0.30	245
	56	45.25	6.6	20		5.25	M5	7	25	50		2.5×10 ⁻⁴	11000			±0.40	540
	68	53.8	7.6	24		5.8	M6	14	60	120		6.5×10 ⁻⁴	19000			±0.45	960
	82	68	9.3	30		8	M8	30	100	200		1.7×10 ⁻³	22000			±0.55	1763
双膜片 DCDE13	19	26.5	3	9	6	1.25	M2.5	1	0.8	1.6	10000	1.9×10 ⁻⁶	430	0.11	1 (单侧)	±0.20	37
	26	33.5	3.3	10.5	7.5	2.5			1.5	3		8.6×10 ⁻⁶	700	0.15		±0.30	86
	29	35.7	3.75	12	6.7	M3	1.5	3	6	1.4×10 ⁻⁵		1200	0.18		2	±0.30	109
	34	38.2	4	7.5	3.35			4	8	2.7×10 ⁻⁵		1700	0.22	1 (单侧)	±0.36	160	
	39	47.7	5	15	9	4.35	M4	3.4	6	12		5.9×10 ⁻⁵	2500		0.24	±0.50	267
	44	48.2			4.6	10			20	9.6×10 ⁻⁵		3000	0.28		±0.60	330	
	56	62.5	6.6	20	12	5.25	M5	7	25	50		3.4×10 ⁻⁴	8500		0.32	±0.80	720
	68	73.6	7.6	24	14	5.8	M6	14	60	120		8.8×10 ⁻⁴	12000		0.32	±0.90	1276
	82	98	9.3	30	22	8	M8	30	100	200		2.5×10 ⁻³	15000		0.52	±1.00	2465

惯性力矩和重量按最大孔径计算。

可选加工	变更h/p孔径		h孔侧键槽加工	p孔侧键槽加工																				
代码	hh() ph()		HK	PK																				
技术说明																								
	选型方法: hh3.1 ph4.5																							
	最小单位0.1																							
	hh须≤ph																							
	选型时须将h(p)变更为hh(ph)																							
	<table><tr><th>D</th><th>hh,ph</th></tr><tr><td>19</td><td>3~8</td></tr><tr><td>26</td><td>4~11</td></tr><tr><td>29</td><td>5~14</td></tr><tr><td>34</td><td>5~15</td></tr><tr><td>39</td><td>8~16</td></tr><tr><td>44</td><td>8~20</td></tr><tr><td>56</td><td>12~25</td></tr><tr><td>68</td><td>14~30</td></tr><tr><td>82</td><td>24~35</td></tr></table>		D	hh,ph	19	3~8	26	4~11	29	5~14	34	5~15	39	8~16	44	8~20	56	12~25	68	14~30	82	24~35		
D	hh,ph																							
19	3~8																							
26	4~11																							
29	5~14																							
34	5~15																							
39	8~16																							
44	8~20																							
56	12~25																							
68	14~30																							
82	24~35																							

当孔径≥6时才能选择键槽加工。



请按图示订货

■ DCDE03-D19-h3-p3

型号		h-p	
代码	D	h	p
DCDE03	19	3	3 4 5 6 6.35 7 8



交期Delivery

5天

发货

○本产品发货时间不含周日

