

梅花式联轴器 ◀ 螺钉固定型/螺钉夹紧型(铝合金)







代码	类型	材质	表面处理	附件
		主体膜片	主体	
CEA01	螺钉固定型	铝合金	阳极氧化	紧定螺钉
CEA21	螺钉夹紧型			内六角圆柱头螺钉

- ① 顺时针和逆时针回转特性一样；
② 补偿径向、角向、轴向偏差。
③ 梅花垫可选通孔，后缀加“-T”。

CEA01

CEA21



型号																
代码	D	h-p (hsp)														
CEA01	14	3 4 5 6 6.35 7														
	20	4 5 6 6.35 7 8 9 9.525 10														
	25	5 6 6.35 7 8 9 9.525 10 11 12														
	30	5 6 6.35 7 8 9 9.525 10 11 12 12.7 13 14 15														
	35	8 9 9.525 10 11 12 12.7 13 14 15 16 17														
	40	8 9 9.525 10 11 12 12.7 13 14 15 16 17 18 19 20 22														
	40L	8 9 9.525 10 11 12 12.7 13 14 15 16 17 18 19 20 22														
	55	12 12.7 13 14 15 16 17 18 19 20 22 24 25 28 30														
	65	14 15 16 17 18 19 20 22 24 25 28 30 32 35 36 38														
	80	19 20 22 24 25 28 30 32 35 36 38 40 42 45														

型号																	
代码	D	h-p (hsp)															
CEA21	14	3	4	5	6	6.35	7										
	20	4	5	6	6.35	7	8	9	9.525	10							
	25	5	6	6.35	7	8	9	9.525	10	11	12						
	30	5	6	6.35	7	8	9	9.525	10	11	12	12.7	13	14	15		
	35	8	9	9.525	10	11	12	12.7	13	14	15	16	17				
	40	8	9	9.525	10	11	12	12.7	13	14	15	16	17	18	19	20	22
	40L	8	9	9.525	10	11	12	12.7	13	14	15	16	17	18	19	20	22
	55	12	12.7	13	14	15	16	17	18	19	20	22	24	25	28	30	
	65	14	15	16	17	18	19	20	22	24	25	28	30	32	35	36	38
	80	19	20	22	24	25	28	30	32	35	36	38	40	42	45		

■ 尺寸性能表

代码	D	L	C	U	A	M	锁紧扭矩 (N·m)	额定扭矩 (N·m)	最大扭矩 (N·m)	最高转速 (r/pm)	惯性力矩 (kg·m ²)	静态扭转刚性 (N·m/rad)	径向弹性常 数(N/mm)	径向偏差 (mm)	角向偏差 (°)	轴向偏差 (mm)	重量 (g)
CEA01	14	22	7.5	7	3.8	M3	0.7	2	4	10000	1.98×10^{-7}	20	368	0.1	1	±0.6	6
	20	30	10.3	9	5.2	M4	1.7	4.8	9.6		1.09×10^{-6}	42	388			±0.8	18
	25	34	11.5	11	5.8	M4		9.5	19		4.26×10^{-6}	95	518			±0.9	32
	30	35	11.7	11.6	5.9	M4		12	24		6.19×10^{-6}	132	630			±1	47
	35	50	18	14	9	M5	4	15	30		2.56×10^{-5}	950	1030			±1.1	90
	40	55	20	15	10	M5		16.5	33		3.34×10^{-5}	1250	1370			±1.2	123
	40L	66	25.5	15	12.8	M5		16.5	33	7000	4.01×10^{-5}	1500	1650			±1.2	150
	55	78	30.5	17	15.3	M6	7	45	90		1.63×10^{-4}	1940	1310			±1.4	346
	65	90	36	18	18	M8	15	100	200		3.69×10^{-4}	3010	1360			±1.5	510
	80	114	46	22	23	M8		250	500	5000	1.04×10^{-3}	5820	1660			±1.8	1010
CEA21	14	22	7.5	7	3.8	M2.5	1	2	4	10000	1.98×10^{-7}	20	368	0.1	1	±0.6	6
	20	30	10.3	9	5.2	M3	1.5	4.8	9.6		1.09×10^{-6}	42	388			±0.8	18
	25	34	11.5	11	5.8	M4	3.4	9.5	19		4.26×10^{-6}	95	518			±0.9	32
	30	35	11.7	11.6	5.9	M4		12	24		6.19×10^{-6}	132	630			±1	47
	35	50	18	14	9	M5	7	15	30		2.56×10^{-5}	950	1030			±1.1	90
	40	55	20	15	10	M5		16.5	33		3.34×10^{-5}	1250	1370			±1.2	123
	40L	66	25.5	15	12.8	M5		16.5	33	7000	4.01×10^{-5}	1500	1650			±1.2	152
	55	78	30.5	17	15.3	M6	14	45	90		1.63×10^{-4}	1940	1310			±1.4	346
	65	90	36	18	18	M8	30	100	200		3.69×10^{-4}	3010	1360			±1.5	532
	80	114	46	22	23	M8		250	500	5000	1.04×10^{-3}	5820	1660			±1.8	1000



请按图示订货

■ CEA01-D20-h5-p8

型号	h-p (hsp)
代码 D	4 5 6 6.35 7 8 9 9.525 10
CEA01 20	



交期Delivery

3天

发货

○本产品发货时间不含周日



www.vipdo.cn 400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌，让采购更便捷，让设计更高效！