




平行线式联轴器 ◀ 螺钉固定型/螺钉夹紧型(铝合金)





代码	类型	材质	表面处理	附件
CBA01	螺钉固定型	铝合金	阳极氧化	坚定螺钉
CBA21	螺钉夹紧型			内六角圆柱头螺钉

- ① 顺时针和逆时针回转特性一样；
② 补偿径向、角向、轴向偏差。

CBA01 螺钉固定型



CBA21 螺钉夹紧型



型号		h-p (h≤p)	
代码	D		
CBA01	12	3 4 4.5 5 6	
	16	3 4 5 6 6.35 7 8	
	20	4 5 6 6.35 7 8 9 9.525 10	
	25	5 6 6.35 7 8 9 9.525 10 11 12	
	32	8 9 9.525 10 11 12 12.7 13 14 15 16	
	40	8 9 9.525 10 11 12 12.7 13 14 15 16 17 18	
	50	12 12.7 13 14 15 16 17 18 19 20	
	63	14 15 16 17 18 19 20 22 24	

型号		h-p (h≤p)	
代码	D		
CBA21	12	3 4 4.5 5	
	16	3 4 4.5 5 6	
	20	4 5 6 6.35 7 8	
	25	5 6 6.35 7 8 9 9.525 10	
	32	8 9 9.525 10 11 12 12.7 13 14	
	40	8 9 9.525 10 11 12 12.7 13 14 15 16 17 18	
	50	12 12.7 13 14 15 16 17 18 19 20	
	63	14 15 16 17 18 19 20 22 24	

■ 尺寸性能表

型号		L	A	M	螺钉紧固扭矩 (N·m)	容许扭矩(N·m)			容许安装偏差		静态扭转刚性 (N·m/rad)	最高回转数 (r/min)	惯性力矩 (kg·m ²)	重量 (g)
代码	D					常用(N·m)	最大(N·m)	偏角(°)	偏心(mm)	轴向位移 (mm)				
CBA01	12	18.5	2.5	M3	0.5	0.4	0.8	2	0.1	±0.2	45	52000	8.3×10 ⁻⁸	3.7
	16	23	3	M3	0.7	0.5	1	2	0.1	±0.3	80	39000	3.3×10 ⁻⁷	8.1
	20	26	3.6	M4	0.7	1	2	2	0.1	±0.3	170	31000	8.9×10 ⁻⁷	14
	25	31	3.6	M4	1.7	2	4	2	0.15	±0.4	380	25000	2.6×10 ⁻⁶	27
	32	41	4.3	M4	1.7	4	8	2	0.15	±0.5	500	19000	9.6×10 ⁻⁶	60
	40	50	6	M6	4	8	16	2	0.2	±0.5	700	15000	3.2×10 ⁻⁵	130
	50	71	10.5	M8	7	13	26	2	0.2	±0.5	1800	12000	9×10 ⁻⁵	266
	63	90	11.3	M8	15	22	44	2	0.2	±0.5	3100	10000	3×10 ⁻⁴	500
CBA21	12	18.5	2.5	M2	0.5	0.4	0.8	2	0.1	±0.2	45	52000	8.3×10 ⁻⁸	3.6
	16	23	3.25	M2.5	1	0.5	1	2	0.1	±0.3	80	39000	3.3×10 ⁻⁷	9.2
	20	26	3.75	M2.5	1	1	2	2	0.1	±0.3	170	31000	8.9×10 ⁻⁷	16
	25	31	4.25	M3	1.5	2	4	2	0.15	±0.4	380	25000	2.6×10 ⁻⁶	28
	32	41	6	M4	2.5	4	8	2	0.15	±0.5	500	19000	9.6×10 ⁻⁶	64
	40	56	8.5	M5	7	8	16	2	0.2	±0.5	700	15000	3.2×10 ⁻⁵	140
	50	71	10.5	M6	12	13	26	2	0.2	±0.5	1800	12000	9×10 ⁻⁵	272
	63	90	13	M8	16	22	44	2	0.2	±0.5	3100	10000	3×10 ⁻⁴	530



请按图示订货

■ CBA01-D12-h5-p6

型号		h-p (h≤p)
代码	D	
CBA01	12	3 4 4.5 5 6
	16	3 4 5 6 6.35 7 8



交期Delivery

3天

发货

○本产品发货时间不含周日

