

同步轮惰轮 ◀ S3M型




采用旋铆工艺安装冲压挡圈，
挡圈尺寸指定或工艺限制无法
加工时，存在车削挡圈的情形；


代码	类型	带轮类型	材质			表面处理
			主体	法兰	轴承	
VTP01	单轴承	S3M	铝合金	钢		本色阳极氧化
VTH01	双轴承					

注：部分产品可能存在用库存改制，追加加工内孔及挡边尺寸，内孔及挡边可能未做表面处理

VTP01 单轴承



VTH01 双轴承



视角标准:第一视角

型号			P.D.	O.D.	F	E	A	W	S	dh	轴承尺寸			
代码	齿数	带轮类型									轴承型号×数量	d	D	B
VTP01 单轴承型 (S3M型)	20	S3M060	19.1	18.34	22	14	7	11	3	9	685ZZ×1	5	11	5
	24		22.92	22.16	25	16			3.5	11	695ZZ×1		13	4
	25		23.87	23.11	28	18			3	13	696ZZ×1	6	15	5
	26		24.83	24.07										
	28		26.74	25.98	30	20								
	30		28.65	27.89	32	23			2.5	17	698ZZ×1	8	19	6
	32		30.56	29.8	35	25								
	36		34.38	33.62	40	28								
	40		38.2	37.44	44	32								
	44		42.02	41.25	48	36								
	48		45.84	45.07	50	38								
	50		47.75	46.98	52	40					6900ZZ×1	10	22	6
	60		57.3	56.53	61	46								

型号			P.D.	O.D.	F	E	A	W	dh	轴承尺寸					
代码	齿数	带轮类型								轴承型号×数量	d	D	B		
VTH01 双轴承型 (S3M型)	20	S3M100	19.1	18.34	22	14	11	15	6	674ZZ×2	4	7	2.5		
		S3M150					17	21	9	685ZZ×2	5	11	5		
	24	S3M100	22.92	22.16	25	16	11	15	11	695ZZ×2	5	13	4		
		S3M150					17	21							
	25	S3M100	23.87	23.11	28	18	11	15	13	696ZZ×2	6	15	5		
		S3M150					17	21							
	26	S3M100	24.83	24.07			11	15							
		S3M150					17	21							
	28	S3M100	26.74	25.98			30	20						11	15
		S3M150												17	21
	30	S3M100	28.65	27.89	32	23	11	15							
		S3M150					17	21							
	32	S3M100	30.56	29.8	35	25	11	15	17			8	19		
		S3M150					17	21							
	36	S3M100	34.38	33.62	40	28	11	15	20	6900ZZ×2		10	22	6	
		S3M150					17	21							
	40	S3M100	38.2	37.44	44	32	11	15							
		S3M150					17	21							
	44	S3M100	42.02	41.25	48	36	11	15							
		S3M150					17	21							
	48	S3M100	45.84	45.07	50	38	11	15							
		S3M150					17	21							
	50	S3M100	47.75	46.98	52	40	11	15							
		S3M150					17	21							
	60	S3M100	57.3	56.53	61	46	11	15	25	6001ZZ×2	12	28	8		
		S3M150					17	21							



请按图示订货

■ VTP01-24-S3M060

型号		
代码	齿数	带轮类型
VTP01	20	S3M060
单轴承型(S3M型)	24	



交期Delivery

5天

发货

本产品发货时间不含周日