

梯形齿同步带轮 ◀ L型(齿距9.525)






型号				材质		表面处理
皮带宽度12.7mm (1/2inch)	皮带宽度19.1mm (3/4inch)	皮带宽度25.4mm (1inch)	皮带宽度38.1mm (1.5inch)	带轮	法兰	
A:14 W:19	A:21 W:26	A:11 W:16	A:14 W:19	铝合金		本色阳极氧化
VPQ01□□L050	VPQ21□□L075	VPQ31□□L100	VPQ41□□L150			黑色阳极氧化
VPQ02□□L050	VPQ22□□L075	VPQ32□□L100	VPQ42□□L150			喷砂无电解镍
VPQ03□□L050	VPQ23□□L075	VPQ33□□L100	VPQ43□□L150			发黑
VPQ04□□L050	VPQ24□□L075	VPQ34□□L100	VPQ44□□L150	S45C	SPCC	无电解镍
VPQ05□□L050	VPQ25□□L075	VPQ35□□L100	VPQ45□□L150			

带轮形状:A型

带轮形状:B型

齿形(ISO标准齿条尺寸)



齿数为60、70时 t=2.0(切割法兰)



- 1.同步轮默认配有机米螺钉出货;
- 2.为保证齿形完整,螺孔打在齿底,当齿数不能等分时,螺孔会打在相邻齿底,此时,螺孔角度略有偏差(可能≠120°);
- 3.部分产品存在改制/追加工,可能存在内孔/挡边追加工后,未表面处理的情况;
- 4.如需防锈,请选用铝合金材质,也可定制SUS304材质,表面处理镀锌的产品。

轴孔规格

H圆孔

P圆孔+螺孔

N新JIS键槽孔+螺孔



型号			带轮 形状	轴孔规格d47(最小单位1)						P.D.	O.D.	D	F	E	带轮公称宽度																																					
代码	齿型	齿数		A型			B型								A	W	L																																			
				H	P	N	H	P	N																																											
VPQ01	L050 L075 L100 L150	12	A B	8~22	8~18	8~22	8~18	36.38	35.62	27	45	30	皮带宽度12.7 L050 A:14 W:19 L:31(39)																																							
VPQ02		14		8~27	8~21	8~26	8~20	42.45	41.68	30	48	35																																								
VPQ03		16		10~32	10~26	10~23	10~28	10~22	48.51	47.75	32	55				40																																				
VPQ04		17		10~32	10~26	10~30	10~24	10~23	51.54	50.78	34																																									
VPQ05		18		10~37	10~29	10~29	10~32	10~26	54.57	53.81	36	61				45																																				
VPQ21		19		12~42	12~34	12~30	12~34	12~28	12~25	57.81	56.84	38				67	50																																			
		20		12~42	12~34	12~30	12~36	12~30	12~26	60.64	59.88	40																																								
VPQ22		21		12~48	12~40	12~32	12~38	12~30	12~26	63.67	62.91	42				70	56	皮带宽度19.1 L075 A:21 W:26 L:38(46)																																		
VPQ23		22		12~52	12~42	12~34	12~41	12~33	12~30	66.7	65.94	45				80	60																																			
VPQ24		24		12~59	12~49	12~41	12~46	12~38		12~30	72.77	72				50	87	67																																		
VPQ25		26		12~59					75.8		75.04																																									
VPQ31		28		12~67	12~57	12~49	12~52	12~42	12~34	78.83	78.07	56	99	80	皮带宽度25.4 L100 A:27 W:32 L:44(53)																																					
		VPQ32		30	12~72	12~62				12~50	14~52							14~42	14~34	90.96	90.2	104	84																													
VPQ33		32		14~76	14~65	14~50	14~59	14~49	14~41	97.02	96.26	63	111	90	皮带宽度38.1 L150 A:40 W:45 L:57																																					
VPQ34		34		14~80		103.08				102.32	123							102																																		
VPQ35		36		14~80			109.15	108.39	71	127	105	140	120	115	注:当齿数为60,72的宽度 25.4的碳钢材料时, 只有 A/D型																																					
VPQ41		38		16~80			115.21	114.45										144	125																																	
		40		16~80			121.28	120.51	152	130																																										
VPQ42		42		16~80			127.34	126.58	160	140	125	190	160																																							
VPQ43		44		16~80			133.4	132.64									154	125																																		
VPQ44	46	16~80		139.47	137.71		151.6	150.83																																												
VPQ45	48	16~80			145.53	144.77										160	140																																			
VPQ45	50	16~80			16~65	16~50	16~67	16~57	16~49	181.91	181.15																																									
VPQ04	L050 L075 L100	60		16~100						A B	16~100																																									
VPQ05		72																																																		
VPQ24																																																				
VPQ25																																																				
VPQ34																																																				
VPQ35																																																				



请按图示订货

VPQ02-L075-50-A-P-d55

型号			带轮形状	轴孔规格dH7(最小单位1)					
代码	齿型	齿数		A型			B型		
VPQ02	L050	50	A	H	P	N	H	P	N
	L075		B	16~80	16~65	16~50	16~67	16~57	16~49



交期Delivery

7天

发货

本产品发货时间不含周日

同步轮
15