


免键梯形齿同步带轮 ◀ L型(齿距9.525)



型号				材质			表面处理		
皮带宽度12.7mm (1/2inch)	皮带宽度19.1mm (3/4inch)	皮带宽度25.4mm (1inch)	皮带宽度38.1mm (1.5inch)	带轮	法兰	衬套	带轮	法兰	衬套
A : 14 W : 19	A : 21 W : 26	A : 27 W : 32	A : 40 W : 45	铝合金	铝合金		本色阳极氧化	发黑	
VAB01□□L050	VAB11□□L075	VAB21□□L100	VAB31□□L150	铝合金	铝合金		发黑	发黑	发黑
VAB03□□L050	VAB13□□L075	VAB23□□L100	VAB33□□L150	S45C	SPCC	S45C			
VAB04□□L050	VAB14□□L075	VAB24□□L100	VAB34□□L150				无电解镀锌		

注：部分产品可能存在用库存改制，追加加工内孔及挡边尺寸，内孔及挡边可能未做表面处理



型号		带轮 形状	轴孔规格dH7(根据胀套孔径表选择)								P.D.	O.D.	F	E	A	W		
代码	齿数		L050		L075		L100		L150									
			E型 ST胀套	F型 SH胀套	E型 ST胀套	F型 SH胀套	E型 ST胀套	F型 SH胀套	E型 ST胀套	F型 SH胀套								
VAB01-L 050 VAB03-L 050 VAB04-L 050	14	E F	8-12(无9)	8 10	10-12 (无9)	8 10	10-12	/	11-12	/	42.45	41.68	48	35	L050 A: 14 W: 19			
	15							10 11		11 12	45.48	44.72	55	40				
	16		10-17 (无9, 13)	10-12 (无9)	10-17 (无9, 13)	10-15	10-17	10-15	11-17	11-15	48.51	47.75	61	45				
	17										51.54	50.78						
	18		54.57	53.81														
19	12-17 (无9, 13)		12	12-17(无9, 13)								57.61	56.84	67	50	L075 A: 21 W: 26		
20									60.64	59.88	67	50						
21	12-25 (无9, 13, 21, 23)			12-25(无9, 13, 21, 23)								63.67	62.91	70	56			
22									66.7	65.94	80	60						
24	12-30 (无9, 13, 21, 23, 26, 27, 29)			12, 13, 14, 15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30								72.77	72	87	67			
25																		
26	12, 13, 14, 15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32			12, 13, 14, 15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32								75.8	75.04	95	75	L100 A: 27 W: 32		
28												78.83	78.07					
30				1213, 14, 15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 35								84.89	84.13					
32				12, 13, 14, 15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32								12-35 (无9, 13, 21, 23, 26, 27, 29, 31)	12-32 (无9, 13, 21, 23, 26, 27, 29)	12-35 (无9, 13, 21, 23, 26, 27, 29, 31)	90.96			90.2
34									97.02	96.26	104	84	L150 A: 40 W: 45					
36									103.08	102.32	111	90						
38	15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32	15, 16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32								15-35 (无21, 23, 26, 27, 29, 31)	15-32 (无21, 23, 26, 27, 29, 31)	15-35 (无21, 23, 26, 27, 29, 31)			109.15	108.39	123	102
40										115.21	114.45	127			105			
42									121.28	120.51	131	110						
44	16, 17, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 35	/	16-35 (无21, 23, 26, 27, 29, 31)	16-32 (无21, 23, 26, 27, 29, 31)	16-35 (无21, 23, 26, 27, 29, 31)	16-35 (无21, 23, 26, 27, 29, 31)	/	/	127.34	126.58	135	115						
46											133.4	132.64	140	120				
48											145.53	144.77	152	130				
50									151.6	150.83	160	140						

胀套孔径尺寸

dH7	容许最大扭矩 N.m		D		(L)
	ST 胀套	SH 胀套	ST 胀套	SH 胀套	
8	16	8.5	25.5	24.5	8.5
10	39	18	30	29	10.5
11	43	20	31	30	
12	48	23	32	31	
14	73	37	35	36	12
15	78	39	36	37	
16	83	42	37	38	13
17	88	45	38	39	
18	154	48	43	40	
19	163	49	45	42	
20	171	97	46	46	14
22	186	110	48	47	
24	206	121	50	49	
25	216	124	52	51	
28	353	141	54	53	15.5
30	382	149	57	56	
32	412	163	59	58	16.5
35	451	173	63	61	

请按图示订货

■ VAB01-L050-14-E-d8

型号		带轮	轴孔规格d H7	
代码	齿数	形状	L050	
VAB01-L050	14	E	E	F
	15	F	8-12	8 10

交期 Delivery

7天 发货

○本产品发货时间不含周日