


# 法兰型无油衬套组件 ◀ 标准型 · 单衬/双衬




| 代码    |       | 类型  |        | 固定座   |           | 衬套材质                 |
|-------|-------|-----|--------|-------|-----------|----------------------|
| 无密封圈  | 带密封圈  |     |        | 材质    | 表面处理      |                      |
| FOC01 | FOC11 | 单衬型 | 圆法兰    | SS400 | 无电解<br>镀锌 | 高力黄铜(SP2)<br>镶嵌固体润滑剂 |
| FOC02 | FOC12 |     | 方法兰    |       |           |                      |
| FOC03 | FOC13 |     | 两面切割法兰 |       |           |                      |
| FOD01 | FOD11 | 双衬型 | 圆法兰    |       |           |                      |
| FOD02 | FOD12 |     | 方法兰    |       |           |                      |
| FOD03 | FOD13 |     | 两面切割法兰 |       |           |                      |


单衬型 FOC01/02/03/11/12/13




双衬型 FOD01/02/03/11/12/13




带防尘圈型




圆法兰型



方法兰型



两面切割法兰型



■ 带防尘圈型建议仅用于f8导向轴

■ 肩部底面与D部之间垂直度在0.02以内

| 型号                                               |     | D           |    | L   |        | L <sub>1</sub> | H   | T  | d <sub>1</sub> | d <sub>2</sub> | t   | P.C.D | W  | F  | A  |
|--------------------------------------------------|-----|-------------|----|-----|--------|----------------|-----|----|----------------|----------------|-----|-------|----|----|----|
| 代码                                               | d   |             |    | 单衬型 | 双衬型    |                |     |    |                |                |     |       |    |    |    |
| 单衬型<br>FOC01 FOC11<br>FOC02 FOC12<br>FOC03 FOC13 | 6   | +0.022<br>0 | 12 | 0   | -0.018 | 22             | 37  | 5  | 3.5            | 6              | 3.1 | 20    | 22 | \  | 20 |
|                                                  | 8   | +0.028<br>0 | 15 | 21  |        | 27             | 47  |    |                |                |     | 24    | 25 |    | 24 |
|                                                  | 10  |             | 19 |     |        |                |     |    |                |                |     | 29    | 30 |    | 29 |
|                                                  | 12  | +0.034<br>0 | 21 | 0   | -0.021 | 32             | 57  | 6  | 4.5            | 7.5            | 4.1 | 32    | 32 | \  | 32 |
|                                                  | 13  |             | 23 |     |        |                |     |    |                |                |     | 33    | 34 |    | 33 |
|                                                  | 16* |             | 28 | 37  | 67     |                |     |    |                |                |     | 38    | 37 | 22 | 31 |
| 双衬型<br>FOD01 FOD11<br>FOD02 FOD12<br>FOD03 FOD13 | 20* | +0.041<br>0 | 32 | 42  | 77     | 37             | 67  | 8  | 5.5            | 9              | 5.1 | 43    | 42 | 24 | 36 |
|                                                  | 25* |             | 40 | 58  | 108    |                |     |    |                |                |     | 51    | 50 | 32 | 40 |
|                                                  | 30* |             | 45 | 68  | 128    |                |     |    |                |                |     | 60    | 58 | 35 | 49 |
|                                                  | 35  | +0.050<br>0 | 52 | 80  | 150    | 68             | 128 | 10 | 6.6            | 11             | 6.1 | 67    | 64 | \  | \  |
|                                                  | 40  |             | 60 |     |        |                |     |    |                |                |     | 78    | 75 |    |    |
|                                                  | 50  |             | 80 |     |        |                |     |    |                |                |     | 98    | 92 |    |    |
|                                                  |     |             |    | 80  | 170    | 90             | 170 | 13 | 9              | 14             | 8.1 |       |    | \  | \  |
|                                                  |     |             |    |     |        |                |     |    |                |                |     |       |    |    |    |

■ 两面切割法兰无带“\*”规格。

## FOC01-d6



请按图示订货

| 型号    |   |             |    |             |
|-------|---|-------------|----|-------------|
| 代码    | d | D           |    |             |
| FOC01 | 6 | +0.022<br>0 | 12 | 0<br>-0.018 |



交期Delivery

4天

发货

○ 本产品发货时间不含周日

www.vipdo.cn 400-098-1117 工厂自动化零件一站式采购平台

汇集国内外知名品牌，让采购更便捷，让设计更高效！