

平键 ◀ 中心沉孔型/中心螺纹沉孔型




代码	类型	材质	抗拉强度	L尺寸公差	
PLF31	中心沉孔型	A型 S45C	600N/mm ² 以上	L	公差
PLF32		SUS304		最短~18	0 -0.43
PLF41		B型 S45C		19~30	0 -0.52
PLF42		SUS304		31~50	0 -0.62
PLF51	中心螺纹沉孔型	C型 S45C		51~80	0 -0.74
PLF52		SUS304		81~110	0 -0.87
PLF61		A型 S45C			
PLF62		SUS304			
PLF71		B型 S45C			
PLF72		SUS304			
PLF81		C型 S45C			
PLF82		SUS304			

中心沉孔型


A型

PLF31/32




B型

PLF41/42



C型


PLF51/52



中心螺纹沉孔型


A型

PLF61/62




B型

PLF71/72



C型

PLF81/82



型号		L																H		d	d1	h	C	
代码	Bh9																							
A型	8	0	15	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100	7		3.3	6	3.3	0.3
PLF31	10	-0.036	15	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100			4.3	7.5	4.3	
PLF32	12		20	25	30	35	40	45	50	55	60	65	70	80	85	90	100		8					
B型	14		30	35	40	45	50	55	60	65	70	80	85	90	100				9	-0.09				
PLF41	15	0	30	35	40	45	50	55	60	65	70	80	85	90	100						5.3	9.5	5.3	0.5
PLF42	16	-0.043	40	45	50	55	60	65	70	80	85	90	100						10					
C型	16		40	45	50	55	60	65	70	80	85	90	100											
PLF51	18		40	45	50	55	60	65	70	80	85	90	100	110					11	0	6.3	11	6.3	
PLF52																			-0.110					

型号		L																	H	拆卸螺 纹M	安装用 螺钉	d1	h	C	
代码	Bh9																								
A型	8	0	15	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100	7		M4	M3	6	3.3	0.3
PLF61	10	-0.036	15	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100	8		M5	M4	8	4.3	
PLF62	12		20	25	30	35	40	45	50	55	60	65	70	80	85	90	100		0						
B型	14		30	35	40	45	50	55	60	65	70	80	85	90	100				9	-0.09					
PLF71	15	0	30	35	40	45	50	55	60	65	70	80	85	90	100				10		M5	M5	10	5.3	0.5
PLF72	14	-0.043	30	35	40	45	50	55	60	65	70	80	85	90	100										
C型	16		40	45	50	55	60	65	70	80	85	90	100												
PLF81	18		40	45	50	55	60	65	70	80	85	90	100	110					11	0					
PLF82																			-0.110						



请按图示订货

PLF31-B8-L15

型号

代码

PLF31

B

8

L

15 20 25 30 35 40



交期Delivery

3天

发货

○本产品发货时间不含周日