


带座磁铁 ◀ 薄型 / 超薄型




代码	类型	磁铁座		磁身		耐热温度	磁极	
		材质	表面处理	材质	表面处理		表面	反面
GYLM32	薄型	SUM24L	无电解镀镍	钴磁铁	/	80℃	N	S
GYLM33			发黑			200℃		
GYLM34			无电解镀镍	钕磁铁		80℃	S	N
GYLM46		SUS416	/	镀镍				
GYLM51			/				N	S
GYLM61		超薄型	SUM22	无电解镀镍	耐热钕磁铁	150℃		
GYLM81	SUS416		/	钕磁铁	镀镍		80℃	N

GYLM32/33/34/46/51/61



GYLM81



型号		B	M	D ₁	D ₂	B ₁	h
代码	D						
钴磁铁 GYLM32 GYLM33	(4)	4	M2	3	2.5	1.5	0.5
	(5)			4	3.5		
钕磁铁 GYLM34 GYLM46 GYLM51	6	6	M3	5	4	2.2	1.5
	8			6(6.5)	5(5.5)		
	10			8	7		
耐热钕磁铁 GYLM61	13	8	M4	11	9.5	1.5	1(1.1)
	16			14	12.5		1.5(1.6)
	20			18	16.5		2.5(2.6)
	25			23	21.5		

吸引力N(kgf)				表面磁通密度高斯(G)				
GYLM32/33	GYLM34	GYLM46	GYLM51/61	GYLM32	GYLM33	GYLM34	GYLM46	GYLM51/61
/	0.62(0.06) 1.27(0.13)	/	/	/	/	2700-3000 2700-3000	/	/
2.9(0.3)	3.9(0.4)	3.9(0.4)	3.9(0.4)	2100-2600	2100-3400	2700-3000	2700-3000	2700-3000
3.9(0.4)	6.9(0.7)	6.9(0.7)	6.9(0.7)	2200-2600	2200-3400	2700-3000	2700-3000	2700-3000
9.8(1.0)	19.6(2.0)	19.6(2.0)	19.6(2.0)	2100-2300	2100-3100	2700-3000	2700-3000	2700-3000
29.4(3.0)	44.1(4.5)	44.1(4.5)	44.1(4.5)	2200-2400	2200-3200	3000-3400	3000-3400	3000-3400
49.0(5.0)	88.3(9.0)	88.3(9.0)	/	2200-2500	2200-3300	3000-3400	3000-3400	/
88.3(9.0)	127.5(13.0)	127.5(13.0)		2300-2600	2300-3400	3300-3500	3300-3500	
127.5(13.0)	196.1(20.0)	196.1(20.0)		2300-2600	2300-3400	3000-3400	3000-3400	

注意:1.GYLM33不适用()内的规格; 2.GYLM33的D₁、D₂、h尺寸为()内的尺寸; 3.吸引力、表面磁通密度是指磁铁单件的值(仅供参考)。

型号		B	D ₁	D ₂	B ₁	h	吸引力N(kgf)	表面磁通密度高斯(G)
代码	D							
GYLM81	6	3	5	4	1.5	1	3.9(0.4)	2700-3000
	8		6	5			6.9(0.7)	2700-3000
	10		8	7			19.6(2.0)	2700-3000
	13	4	11	9.5	2	1.5	44.1(4.5)	3000-3400

注意:吸引力、表面磁通密度是指磁铁单件的值(仅供参考)。



请按图示订货

GYLM32-D4

型号

代码

D

GYLM32

(4)



交期Delivery

3天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌, 让采购更便捷, 让设计更高效!