



欧标40系列 ◀ 连接配件 挤压压座

系列码	材质	表面处理
XCCB01	A6063-T5	喷砂氧化


- 用于型材固定角度的外连接，可固定封板。
- 可来图定制。





XCCB01-408-4530




XCCB01-408-4570




XCCB01-408-45110





XCCB01-408-3530




XCCB01-408-3570




XCCB01-408-35110





XCCB01-408-5530




XCCB01-408-5570




XCCB01-408-55110





XCCB01-408-5030




XCCB01-408-5070




XCCB01-408-50110




XCCB01-408-6030



XCCB01-408-6070





XCCB01-408-60110




视图标准：第三视角


XCCB01-408-8030





XCCB01-408-8070




XCCB01-408-80110




XCCB01-408-80B30





XCCB01-408-80B70




XCCB01-408-80B110




XCCB01-408-9030





XCCB01-408-9070




XCCB01-408-90110




XCCB01-408-80A30





XCCB01-408-80A70




XCCB01-408-80A110




XCCB01-408-70A30



XCCB01-408-70A70



XCCB01-408-70A110



视图标准：第三视角

欧标40系列 ◀ 连接配件 挤压角座

系列码	型材类型	规格	重量(g/pcs)
XCCB01	408	4530	36.80
		4570	87.00
		45110	135.00
		3530	31.80
		3570	73.00
		35110	116.00
		5530	68.00
		5570	159.00
		55110	250.00
		5030	60.00
		5070	141.00
		50110	222.00
		6030	72.00
		6070	172.00
		60110	268.00

系列码	型材类型	规格	重量(g/pcs)
XCCB01	408	8030	113.00
		8070	269.00
		80110	416.00
		80B30	137.00
		80B70	320.00
		80B110	502.00
		9030	139.00
		9070	324.00
		90110	509.00
		80A30	88.00
		80A70	207.00
		80A110	325.00
		70A30	102.00
		70A70	241.00
		70A110	379.00



请按图示订货

■ XCCB01-408-4530-S

系列码	型材类型	规格	加工项目/配置附件
XCCB01	408	4530	S




交期Delivery

5天

发货

○ 本产品发货时间不含周日

■ 加工项目/配置附件

加工项目/配置附件	代码	说明
截面螺纹孔加工	S	 在角座侧面上加工安装面板用的螺纹孔(单面M5螺纹孔深度15mm) 螺纹孔位置
适配螺栓, T型螺母和垫片	SE	螺栓: YWE02-M6-L12 T型螺母: XCNA45-408-M6 垫片: YWS02-6

■ 加工项目/配置附件指定方法, 见订货范例。

使用示例:

