



带法兰直线轴承 ◀ 标准型 · 单衬型




类型			外壳			滚珠	保持器	使用环境	附件
圆法兰型	方法兰型	两面切割法兰型	材质	硬度	表面处理	材质	材质	温度	
ELP01	ELP21	ELP31	相当于SUJ2	58HRC ~	\	SUJ2	树脂	-20~80℃	无密封圈 密封圈材质 丁腈橡胶
ELP02	ELP22	ELP32							
ELP03	ELP23	ELP33							
ELP04	ELP24	ELP34	相当于SUS440C	56HRC ~	\	SUS440C	不锈钢	-20~120℃	
ELP05	ELP25	ELP35							

圆法兰型





方法兰型



两面切割/法兰型

d=3~13

d=16~50



型号		D			L	H	T	P	K	t	P.C.D.	W	F	A	偏心 (最大)	滚珠 列数	*垂直度	基本额定负载(N)		重量(g)					
代码	d	尺寸	表面处理															C(动)N	Co(静)N	圆法兰型	方法兰型	两面切削 法兰型			
			无	有																					
ELP01	6	0 -0.009	12	0	0	19	±0.3	28	5	3.5	6	3.1	20	22	20	0.012	4	0.012	206	265	24	18	21		
ELP02	8		15	-0.013	-0.018	24		32					24	25					24	265	380	37	29	33	
ELP03	10		19			29		40					29	30					—	29	372	549	72	52	64
ELP04	12		21	0	0	30		42					32	32					32	412	598	76	57	68	
ELP05	13	0 -0.010	23	-0.016	-0.021	32	43	6	4.5	7.5	4.1	32	34	33	0.015	5	0.015	510	784	88	72	81			
ELP22	16		28			37	48	38	37	22	31	775	1180	120				104	112						
ELP23	20		32	0	0	42	54	8	5.5	9	5.1	43	42	24				36	882	1370	180	145	167		
ELP24	25		40	-0.019	-0.025	59	62					51	50	32				40	980	1570	340	300	325		
ELP25	30	0 -0.012	45			64	74	10	6.6	11	6.1	60	58	35	49	0.020	6	0.020	1570	2740	470	375	388		
ELP32	35		52	0	0	70	82					67	64	38	55				1670	3140	650	560	575		
ELP33	40		60	-0.022	-0.030	80	96	13	9	14	8.1	78	75	45	64				2160	4020	1060	880	913		
ELP34	40		80			100	116					98	92	56	80				3820	7940	2200	2000	2037		

■注：“*”D部与法兰安装安装面的垂直度



请按图示订货

■ ELP01-d8

代码

d

ELP01

6

0

8

-0.009



交期Delivery

4天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台