



线性滚珠衬套 ◀ 法兰型·单衬型/双衬型



代码			结构	外壳		材质		使用环境温度
圆法兰	方法兰	两面切割法兰型		材质	硬度	滚珠	保持器	
EVC01	EVC21	EVC31	单衬型	SUJ2	58HRC~	SUJ2	A5052S	-20~80℃
EVD01	EVD21	EVD31	双衬型					

单衬型





双衬型



圆法兰型

方法兰型

两面切割法兰型



型号		D		L	H	T	P	K	t	P.C.D	W	F	A	最大行程		滚珠列数		Q		偏心	垂直度	基本额定负载									
代码	d													单衬	双衬	单衬	双衬	单衬	双衬			C(动)N	Co(静)N	单衬	双衬	单衬	双衬				
EVC01 EVC21 EVC31 EVD01 EVD21 EVD31	6	0 -0.009	12	0	19	28	5.0	3.5	6.0	3.1	20	22	20	15	7	3	6	8.3	12.3	0.012	0.015	210	333	164	328						
	8		15	-0.013	24													32	24			25	24	24	8	8.8	16.8	323	512	278	556
	10		19		29													40	29			30	29	30	8	10.8	21.8	499	793	408	815
	12		21	0	30													42	32			32	32	32	8	10.4	22.4	722	1146	579	1157
	13		23	-0.016	32													43	33			34	33	34	10	11.4	23.4	773	1226	634	1268
	16	28		37	48	38	37	22	31	40	16	12.8	24.8	1330	2112	1029	2058														
	20	0 -0.010	32	0	42	54	8.0	5.5	9.0	5.1	43	42	24	36	46	28	14.8	23.8	1609	2554	1517	3035									



请按图示订货

■ EVC01-d8

型号			
代码	d		
EVC01	6	0	
	8	-0.009	



交期Delivery

4天 发货

○本产品发货时间不含周日