

角接触球轴承

单列·不配对型
双列组合·DF/DB配对型




■出厂前未封入润滑脂，请在使用前封入。


代码	类型	轴承类型代号	轴承精度	轴承材质 国标 相当	接触角
DBAC11	单列型	经济型	GB/T 307.1 0级	GCr15	25°
GBAC01		标准型	GB/T 307.1 5级		
DBAD11	双列组合型	经济型	GB/T 307.1 5级		
GBAD01		标准型	GB/T 307.1 5级		

双列组合型
DBAD11/GBAD01



-DB(反面)




安装图




单列型 DBAC11/GBAC01



-DF(正面)



安装图



型号		d	D	B	r min	n min	基本额定负载		容许转速 rpm(参考)	作用点 a	安装尺寸			重量(g) (参考)
代码	轴承代码						Cr(动)kN	CoR(静)kN			db min	da max	r1 max	
DBAC11 GBAC01	7000	10	26	8	0.3	0.15	5.35	2.6	23200	9.2	12.5	23.5	0.3	23
	7200		30	9	0.6	0.3	5.4	2.71	22400	10.3	15	25	0.6	29
	7001	12	28	8	0.3	0.15	5.8	2.98	20800	9.8	14.5	25.5	0.3	25
	7201		32	10	0.6	0.3	8	4.05	20000	11.4	17	27	0.6	35
	7002	15		9	0.3	0.15	6.1	3.45	18400	11.3	17.5	29.5	0.3	
	7202		11	0.6	0.3	8.65	4.65	17600	12.7	20	30	0.6	46	
	7003	17	35	10	0.3	0.15	6.4	3.8	16800	12.5	19.5	32.5		0.3
	7203		40	12	0.6	0.3	10.8	6	15200	14.2	22	35		0.6
	7004	20	42	12	0.6	0.3	10.8	6.6	14400	14.9	25	37		80
	7204		47	14	1	0.6	14.5	8.3	13600	16.7	26	41	1	100
	7005	25	52	12	0.6	0.3	11.3	7.4	12800	16.4	30	42	0.6	93
	7205		52	15			16.2	10.3	11200	18.6	31	46		125
	7006	30	55	13	1		14.5	10.1	10400	18.8	36	49		135
	7206		62	16			22.5	14.8	9600	21.3		56		193
	7207	35	72	17		0.6	29.7	20.1	8000	23.9	42	65	1	287
	7208	40	80	18			35.5	25.1	7600	26.3	47	73		375
	7209	45	85	19			39.5	28.7	6800	28.3	52	78		411
	7210	50	90	20			41.5	31.5	6320	30.2	57	83		466

型号			d	D	B	r min	n min	基本额定负载		容许转速	作用点 a		安装尺寸						重量 (g)	
代码	轴承代码	两列组合形式						Cr(动)kN	Cor(静)kN	rpm(参考)	DB	DF	DB			DF				
													dbmin	da max	h max	dbmin	da max	h max		
DBAD11 GBAD01	7000	DB (反面) DF (正面)	10	26	8	0.3	0.15	8.75	5.2	18400	18.4	2.4	12.5	24.8	0.3	11.2	23.5	0.15	46	
	7200			30	9	0.6	0.3	8.8	5.4	17600	20.5	2.5	15	27.5	0.6	12.5	25	0.3	58	
	7001		12	28	8	0.3	0.15	9.4	5.95	16800	19.5	3.5	14.5	26.8	0.3	13.2	25.5	0.15	50	
	7201			32	10	0.6	0.3	13	8.05	16000	22.7	2.7	17	29.5	0.6	14.5	27	0.3	70	
	7002		15	9	0.3	0.15	9.95	6.85	14400	22.6	4.6	17.5	30.8	0.3	16.2	29.5	0.15	70		
	7202			35	11	0.6	0.3	14	9.3	13600	25.4	3.4	20	32.5	0.6	17.5	30	0.3	92	
	7003		17	35	10	0.3	0.15	10.4	7.65	13600	25	5	19.5	33.8	0.3	18.2	32.5	0.15	92	
	7203			40	12	0.6	0.3	17.6	12	12000	28.5	4.5	22	37.5		19.5	35		128	
	7004	DB (反面)	20	42	12	0.6	0.3	13.2	12.000	12000	29.9	5.9	25	39.5	0.6	22.5	37	0.3	160	
	7204			47	14	1	0.6	23.5	16.6	10400	33.3	5.3	26	42	1	25	41	0.6	200	
	7005		25	52	15	0.6	0.3	18.3	14.8	9600	32.8	8.8	30	44.5	0.6	27.5	42	0.3	186	
	7205			52	15			26.3	20.5	8800	37.2	7.2	31	47		30	46		250	
	7006		30	55	13	1		23.6	20.2	8800	37.5	11.5	6	50		35	49	0.6	270	
	7206			62	16			36.5	29.5	7840	42.6	10.6	36	57		56	56		386	
	7207		DB (反面)	35	72	17	1.1	0.6	48.5	40	6800	47.9		42	67	1	/	/	/	574
	7208				80	18			57.5	50.5	6000	52.6	47	75	750					
7209	85	19			64.5	57.5			5520	56.5	52	80	822							
7210	90	20			67	63			5040	60.4	57	85	932							

DBAD11-7000-DB



请按图示订货

型号

代码

轴承型号

两列组合形式

DBAD11

7000

DB

DF



交期Delivery

3天

发货

○本产品发货时间不含周日