





杆端关节轴承 ◀ 内螺纹 . 外螺纹 . 铜基润滑型



代码	类型	杆端		衬垫	内圈	
		材质	表面处理	材质	材质	热处理
BGJ01	内螺纹	碳钢	镀环保白锌	铜	碳钢	淬火
BGJ11	外螺纹					
BGJ02	内螺纹	SUS304	/	SUS304	SUS304	/
BGJ12	外螺纹					

内螺纹 BGJ01/02

外螺纹 BGJ11/12



内螺纹轴承

型号		螺纹 旋向	d	B	dk	C1	d2	G(6H)	h	L3 (min)	L4 (max)	L5	W	d4	d5	R1 (min)	a° (≈)	额定负荷 (KN)		重量 (kg)
代码	轴承规格																	动负荷	静负荷	
BGJ01 BGJ02	SI5TK	R (右旋)	5	8	11.11	6	18	M5×0.8	27	10	36	4	9	8.5	11	0.3	13	4.6	4.8	0.016
	SI6TK		6	9	12.7	6.75	20	M6×1.0	30	12	40	5	11	10	13		13	6.1	6.5	0.022
	SI8TK		8	12	15.875	9	24	M8×1.25	36	16	48	6	14	12.5	16		14	8.5	9.5	0.047
	SI10TK		10	14	19.05	10.5	28	M10×1.5	43	20	57	6.5	17	15	19	0.6	13	9.7	12	0.077
	SI10TK-1		12	16	22.225	12	32	M10×1.25 M12×1.75 M12×1.25	50	22	66	8	19	17.5	22		13	10.6	15	0.100
	SI12TK		14	19	25.4	13.5	36	M14×2.0 M14×1.5	57	25	75	10	22	20	25		16	17	22	0.160
	SI14TK	L (左旋)	16	21	28.575	15	42	M16×2.0 M16×1.5	64	28	85	12	27	22	27	1.0	15	19.7	27	0.220
	SI16TK-1		18	23	31.75	16.5	44	M18×1.5	71	32	93	14	30	25	31		15	31.3	35	0.320
	SI20TK		20	25	34.925	18	50	M20×1.5	77	33	102	16	32	27.5	34		14	29.8	40	0.420
	SI22TK		22	28	38.1	20	54	M22×1.5	84	37	111	18	36	30	38		15	40.2	48	0.488
	SI25TK		25	31	42.86	22	60	M24×2.0	94	42	124	20	36	33.5	42		15	44	55	0.540
	SI28TK		28	35	47.63	24	66	M27×2.0	103	51	136	23	41	37	46		15	52.2	65	0.720
BGJ01	SI30TK		30	37	50.8	25	70	M30×2.0	110	51	145	15	41	40	50	1.0	17	60.2	78	0.820
	SI30TK-1		35	43	57.15	28	81	M36×2.0	125	56	165.5	17	50	46	58		16	/	/	1.600
	SI35TK		40	49	66.67	33	91	M42×2.0	142	60	187.5	19	55	53	65		17	/	/	2.400
	SI40TK		50	60	82.5	45	117	M48×2.0	160	65	218.5	23	65	65	75		12	/	/	5.000
	SI50TK																			



www.vipdo.cn 400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌, 让采购更便捷, 让设计更高效!

杆端关节轴承 ◀ 内螺纹 . 外螺纹 . 铜基润滑型

■ 外螺纹型

型号		螺纹旋向	d	B	dK	Ci (max)	d2 (max)	G(6H)	h	L1 (min)	L2 (max)	R1 (min)	a°≈	额定负荷(KN)		重量 (kg)
代码	轴承规格													动负荷	静负荷	
BGJ11 BGJ12	SA5TK	R (右旋) L (左旋)	5	8	11.11	6	18	M5x0.8	33	19	42	0.3	13	4.4	4.6	0.013
	SA6TK		6	9	12.7	6.75	20	M6x1.0	36	21	46			4.5	4.8	0.015
	SA8TK		8	12	15.875	9	24	M8x1.25	42	25	54			5.8	6.5	0.034
	SA10TK		10	14	19.05	10.5	28	M10x1.5	48	28	62			9.7	12	0.071
	SA12TK		12	16	22.225	12	32	M12x1.75	54	32	70	0.6	13	10.6	15	0.11
	SA14TK		14	19	25.4	13.5	36	M14x2.0	60	36	78			16	17	0.13
	SA16TK		16	21	28.575	15	42	M16x2.0	66	37	87			15	19.7	0.22
	SA16TK-1		16	21		15	42	M16x1.5	66	37	87			15	19.7	0.22
	SA18TK		18	23	31.75	16.5	44	M18x1.5	72	41	94		14	15	31.3	0.29
	SA20TK		20	25	34.925	18	50	M20x1.5	78	45	103			29.8	40	0.36
	SA22TK		22	28	38.1	20	54	M22x1.5	84	48	111			40.2	48	0.49
	SA25TK		25	31	42.86	22	60	M24x2.0	94	55	124		15	44	55	0.65
	SA28TK		28	35	47.63	24	66	M27x2.0	103	62	136			52.2	65	0.87
	SA30TK		30	37	50.8	25	70	M30x2.0	107	66	145			17	60.2	1.1
BGJ11	SA35TK		35	43	57.1	28	81	M36x2.0	125	85	180.5	1.0	16	—	—	1.64
	SA40TK		40	49	66.6	33	91	M42x2.0	142	90	195.5		17			2.4
	SA50TK		50	60	82.5	45	117	M48x2.0	160	105	243.5		12			4.8

■ BGJ01-SI5TK-R



请按图示订货

型号		螺纹旋向	d
代码	轴承规格		
BGJ01	SI5TK	R(右旋) L(左旋)	5



交期Delivery

3天

发货

○ 本产品发货时间不含周日

