



圆柱滚子轴承 ◀ 内圈无挡边/内圈单挡边/外圈无挡边




内圈无挡边
BDN01




(安装图)




内圈单挡边
BDN02




(安装图)



外圈无挡边
BDN11



(安装图)



内圈无挡边

代码	型号	d	D	Di	B	n (min)	C3 (min)	F	额定载荷		极限转速(r/min)		安装尺寸				重量值 kg(参考)
									Cr(动)KN	Cor(静)KN	脂润滑	油润滑	da(min.)	Da(max.)	ra(max.)	rb(max.)	
BDN01	306EM	30	72	58.5	19	1.1	1.1	40.5	51.6	48.4	9000	11000	36.5	65.5	1.0	1.0	0.360
BDN01	207EM	35		60.7	17		0.6	44.0	48.7	48.2	8500	10000	39.0	65.5		0.6	0.296
BDN01	307EM	40	80	66.3	21	1.5	1.1	46.2	65.0	53.3	8000	9500	41.5	72.0	1.5	1.0	0.472
BDN01	308EM	45	90	75.4	23		1.5	52.0	80.4	78.0	6700	8000	48.0	82.0		1.5	0.636
BDN01	209EM	45	85	72.1	19	1.1	1.1	54.5	61.3	64.1			51.5	78.5	1.0	1.0	0.424
BDN01	309EM	50	100	83.6	25	1.5	1.5	58.5	97.6	98.3	6300	7500	53.0	92.0	1.5	1.5	0.873
BDN01	210EM	50	90	77.1	20	1.1	1.1	59.5	64.1	69.3			56.5	83.5	1.0	1.0	0.482
BDN01	310EM	50	110	91.7	27	2.0	2.0	65.0	110.0	113.0	5000	6000	59.0	101.0	2.0	2.0	1.120

内圈单挡边

代码	型号	d	D	D1	d1	B	n(min)	F	额定载荷		极限转速(r/min)		安装尺寸			重量值 kg(参考)
									Cr(动)KN	Cor(静)KN	脂润滑	油润滑	da(min.)	Da(max.)	ra(max.)	
BDN02	205EM	25	52	43.5	34.7	15	1.0	31.5	28.7	27.0	11000	14000	29.0	47.0	1.0	0.130
BDN02	207EM	35	72	60.7	48.3	17		44.0	48.7	48.2	8500	10000	39.0	65.5		0.296
BDN02	209EM	45	85	72.1	59.2	19		54.5	61.3	64.1	6700	8000	51.5	78.5		0.424
BDN02	210EM	50	90	77.1	64.2	20		59.5	64.1	69.3	6300	7500	56.5	83.5		0.482

外圈无挡边

代码	型号	d	D	d1	B	F3(min)	E	额定载荷		极限转速(r/min)		安装尺寸			重量值 kg(参考)
								Cr(动)KN	Cor(静)KN	脂润滑	油润滑	da(min.)	Da(max.)	ra(max.)	
BDN11	N207EM	35	72	48.3	17	0.6	64.0	48.7	48.20	8500	10000	66.0	1.0	0.6	0.296
BDN11	N309EM	45	100	64.7	25	1.5	88.5	97.6	98.30	6300	7500	91.0	1.5	1.5	0.873
BDN11	N310EM	50	110	71.2	27	2.0	97.0	110.0	113.00	5000	6000	99.0	2.0	2.0	1.120

kgf=Nx0.101972



请按图示订货

BDN01-306EM

代码	型号	d	D	L
BDN01	306EM	30	72	58.5



交期Delivery

3天 发货

○ 本产品发货时间不含周日

轴承
关节
轴承 26

www.vipdo.cn 400-098-1117 工厂自动化零件一站式采购平台

汇集国内外知名品牌，让采购更便捷，让设计更高效！

P858