



侧边安装型导向轴支座 ◀ 标准型/开口型





代码	类型	材质		表面处理	附件
		国标	相当		
ZFV01	标准型	45	S45C	发黑	1个内六角紧定螺钉
ZFV02				无电解镀锌	1个内六角紧定螺钉(不锈钢)
ZFS01	开口型	0Cr18Ni9	SUS304	发黑	1个内六角圆柱头螺钉
ZFS02				无电解镀锌	1个内六角圆柱头螺钉(不锈钢)
ZFS06				/	
ZFS08				本色阳极氧化	

注:如对防锈有要求,请优先选用不锈钢材质、铝合金材质或喷细砂无电解镀锌产品。

标准型
ZFV01/02



开口型
ZFS01/02/06/08



开口型, 安装孔D的公差H7为开口加工前的公差, 开口加工后由于有内部应力释放, 公差有可能增至H8左右, 不影响客户使用。

型号			H	L	H ₁	H ₂	T	L ₁	d	M		
代码	D _{h7}											
ZFV01 ZFV02	8	+0.015 0	25 30	22	H+8.8	5	12	10	4.5	4		
	10		25 30		H+9.8							
	12	+0.018 0	25 30	25	H+10.8			14				
	13		25 30		H+11.8			16				
	15		25 30 40	28	H+14.8							
	16		25 30 40									
	18	25 30 40 50	32	H+17.8	7	16	18	6.6	6			
	20	25 30 40 50					38			H+19.8	24	
	25	30 40 50	50	H+22.8							10	22
	30	30 40 50 60					H+24.8					
	35	+0.025 0	40 50 60	H+29.8								
	40		40 50 60									

型号		H			L	H ₁	H ₂	T	L ₁	E	d	M	d ₂	d ₁	h	N							
代码	D _{h7}																						
ZFS01 ZFS02 ZFS06 ZFS08	8	20	25	30	22	H+15.8	5	12	10	11	4.5	M4深8	4.5	8	4.7	1.2~2.3							
	10	20	25	30																			
	12	20	25	30																			
	13	20	25	30	25	H+17.8			14	13													
	15	25	30	40																			
	16	25	30	40																			
	18	25	30	40	50	32	H+25.8	7	16	18	18	6.6	M6深12	6.6	11	6.7							
	20	25	30	40	50																		
	25	30	40	50																			
	30	30	40	50	60	38	H+27.8			10	22						32	24	9	M8深16	9	14	9.2
35	40	50	60																				
40	40	50	60																				



请按图示订货

■ ZFV02-D8-H25

型号			H
代码	Dh7		
ZFV02	8	+0.015 0	25



交期Delivery

6天

发货

○本产品发货时间不含周日