


全螺纹六角头螺栓



代码	类型	螺纹	材质	表面处理	硬度	强度等级	适用标准
YWF01	全牙	粗牙	SCM435	发黑	32-39HRC	8.8	DIN 933-1987
YWF02			SUS304	/	/	A2-70	GB/T 5783-2016 ISO 4017-2011
YWF03		细牙	ML40Cr	发黑	/	12.9	GB/T 5786-2000



强度等级是指螺栓的抗拉强度。

例：8.8 表示屈服点或耐力的最小值为抗拉强度的80%

例：A2-70 表示抗拉强度的最小值为800N/MM²

表示抗拉强度的最小值为700N/MM²

钢种分类为A2(奥氏体不锈钢)

型号		L														P螺距	Z		E	
代码	M																max	min		
YWF01	5	8	10	12	16	20	25	30	35	40	45					0.8	3.65	3.35	8	
	6	10	12	16	20	25	30	35	40	45	50	55	60	65	70	75	4.15	3.85	10	
	8	12	16	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	13	
	10	16	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	6.56	6.22	17
	12	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	110	120	130	19
	16	30	35	40	45	50	55	60	65	70	75	80	90	100	110	120	130	10.18	9.82	24

型号		L															P螺距	Z	E		
代码	M																				
YWF02	4	8	10	12	16	20	25	30	35	40	45						0.7	2.8	7		
	5	8	10	12	16	20	25	30	35	40	45	50						0.8	3.5	8	
	6	10	12	16	20	25	30	35	40	45	50	55	60	65	70	75	1	4	10		
	8	12	16	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	1.25	5.3	13
	10	16	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	1.5	6.4	17	
	12	20	25	30	35	40	45	50	55	60	65	70	75	80	90	100	1.75	7.5	19		

型号		L												P螺距	Z		E	
代码	M														max	min		
YWF03	8	16	20	25	30	35	40	45	50					1	5.45	5.15	13	
	10	20	25	30	35	40	45	50					6.58		6.22	16		
	12	25	30	35	40	45	50	55	60						7.68	7.32	18	
	14	30	35	40	45	50	55	60					8.98		8.62	21		
	16	35	40	45	50	55	60	65	70					1.5	10.18	9.82	24	
	18	35	40	45	50	55	60	65	70						11.715	11.285	27	
	20	30	35	40	45	50	55	60	65	70	75	80	12.715		12.285	30		
	22	45	50	55	60	65	70	75	80						14.215	13.785	34	
	24	40	45	50	55	60	65	70	75	80	90					2	15.215	14.785



请按图示订货

YWF01-M5-L8

型号		L											
代码	M												
YWF01	5	8	10	12	16	20	25	30	35	40	45		



交期Delivery

3天

发货

○本产品发货时间不含周日

