


梯形齿同步带轮 ◀ AT10型(齿距10)


型号						材质		表面处理
皮带宽度15mm	皮带宽度20mm	皮带宽度25mm	皮带宽度30mm	皮带宽度40mm	皮带宽度50mm	带轮	法兰	
A:16.5 W:22.5	A:21.5 W:27.5	A:26.5 W:32.5	A: 32 W:37	A:43 W:48	A:53 W:58	铝合金	S45C SPCC	本色阳极氧化
VPY01□□AT10150	VPY21□□AT10200	VPY31□□AT10250	VPY41□□AT10300	VPY51□□AT10400	VPY61□□AT10500			黑色阳极氧化
VPY02□□AT10150	VPY22□□AT10200	VPY32□□AT10250	VPY42□□AT10300	VPY52□□AT10400	VPY62□□AT10500			喷砂无电解镀锌
VPY03□□AT10150	VPY23□□AT10200	VPY33□□AT10250	VPY43□□AT10300	VPY53□□AT10400	VPY63□□AT10500	S45C SPCC		发黑
VPY04□□AT10150	VPY24□□AT10200	VPY34□□AT10250	VPY44□□AT10300	VPY54□□AT10400	VPY64□□AT10500			无电解镀锌
VPY05□□AT10150	VPY25□□AT10200	VPY35□□AT10250	VPY45□□AT10300	VPY55□□AT10400	VPY65□□AT10500			




标准齿形



带轮形状: A形



带轮形状: B形




① $f = (W - A) / 2$; ② 当带轮形状为B形时, $U = (L - W) / 2$, 当 $U \neq$ 整数时, 舍去小数取整。

■ 轴孔规格

H 圆孔



P 圆孔+螺孔




N 新JIS键槽+螺孔
C 旧JIS键槽+螺孔




键槽尺寸详见
同步轮产品简介

V 台阶孔




F 台阶孔(轮毂侧沉孔)



仅适用于B形

Y 两端台阶孔



仅适用于A形

■ 轴孔P.N.C螺孔尺寸表

轴孔内径 dH7	M	附件 紧固螺钉
10~12	M4	M4×3
13~17	M5	M5×4
18~30	M6	M6×5
31~45	M8	M8×6
46~70	M10	M10×8



当同步轮材质为S45C时,
挡圈存在折边式。



视角标准: 第一视角

型号		带轮 形状	轴孔规格dH7(最小单位1)										轴孔V、F		轴孔Y (最小单位1)		P.D.	O.D.	D	F	E	带轮 公称宽度			
代码	齿数		A形					B形					Z(最小单位1)		J (最小单位0.1)	Q-R						S-T	A	W	L
			H	P	N·C	V	Y	H	P	N·C	V·F	A形	B形	A											
铝合金材质		12	8-23	8-18	8-18	8-21	8-21	/	/	/	/	10-23	/	A形时 3.0≤J≤W-3.0 B形时 3.0≤J≤L-3.0	10-23	38.2	36.35	/	40	27	皮带宽度15 AT10150 A:16.5 W:21.5 L38(40)	皮带宽度20 AT10200 A:21.5 W:27.5 L43(48)			
		14	10-32	10-26	10-26	10-30	10-30	10-24	10-18	10-28	12-32	12-30	12-32		44.56	42.70	34	52	36						
	VPY01	VPY02	15	10-33	10-26	10-26	10-31	10-31	10-25	10-20	10-29	12-33	12-31		12-33	47.75	45.90								
	VPY21	VPY22	16	12-36	12-30	12-30	12-34	12-34	12-31	12-25	12-20	12-29	14-36		14-31	14-36	50.93	49.05	35	58				40	
	VPY31	VPY32	18	12-41	12-30	12-30	12-39	12-39	12-31	12-25	12-20	12-29	14-41		14-31	14-41	57.30	55.45		61				45	
	VPY33	VPY41	20	12-46	12-40	12-40	12-44	12-44	12-36	12-30	12-25	12-34	14-46		14-36	14-46	63.66	61.80	40	67				50	
	VPY42	VPY43	22	12-56	12-48	12-48	12-54	12-54	12-36	12-30	12-25	12-34	14-56		14-36	14-56	70.03	68.15		80				60	
S45C材质		24	12-63	12-50	12-50	12-61	12-61	12-38	12-32	12-32	12-44	14-63	14-46	14-63	76.39	74.55				皮带宽度25 AT10250 A:26.5 W:32.5 L48(50)	皮带宽度30 AT10300 A:32 W:37 L52(57)				
		25	12-63	12-50	12-50	12-61	12-61	12-38	12-32	12-44	14-63	14-46	14-63	79.58	77.70	50	87	67							
		26	12-63	12-50	12-50	12-61	12-61	12-38	12-32	12-44	14-63	14-46	14-63	82.76	80.90										
		28	12-68	12-57	12-55	12-66	12-66	12-45	12-40	12-53	14-68	14-55	14-68	89.13	87.25		95	75							
	VPY04	VPY05	30	12-76	12-65	12-65	12-74	12-74	12-45	12-40	12-53	14-76	14-55	14-76	95.49	93.65		104	84						
	VPY14	VPY15	32	20-80	20-70	20-55	20-80	20-80	20-55	20-45	20-40	20-53	22-82	20-55	22-82	101.86	100.00	60	111				90		
	VPY24	VPY24	36	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-94	20-55	22-94	114.59	112.75		123				102		
		40	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-95	20-55	22-95	127.32	125.45		135	115	注:齿数为30~60时 只适用()内尺寸					
	VPY44	VPY45	44	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-95	20-55	22-95	140.06	138.20		152				130		
	VPY54	VPY55	48	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-95	20-55	22-95	152.79	150.95		160				140		
	VPY64	VPY65	50	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-95	20-55	22-95	159.15	157.30	100	170				150		
		60	20-85	20-70	20-55	20-85	20-85	20-55	20-45	20-40	20-53	22-95	20-55	22-95	190.99	189.1		200	180						

注意事项: ① 轴孔规格H/V/F/Y时, 无螺孔。② 孔径8/9/11/13/14/17/21~29/31/32/46~49不适用轴孔规格C, ③ 齿数为30~60时只适用()内尺寸

④ 选购新JIS键槽+螺孔的轴孔直径d10时, 键槽尺寸可选择N-d10或N-d10K(请参阅同步轮产品简介)。



请按图示订货

■VPY01-AT10150-20-A-H-d8

型号			带轮 形状	轴孔规格dH7(最小单位1)				
代码	齿型	齿数		A形				
				H	P	N-C	V	Y
VPY01	AT10150	20	A	5~14	5~10	8~10	5~12	5~12



交期Delivery

5天

发货

本产品发货时间不含周日