


# 压缩弹簧 ◀ 外径基准型(不锈钢)



| 代码 | 类型 | 材质 |    | 允许位移量 | 弹簧常数公差 |
|----|----|----|----|-------|--------|
|    |    | 国标 | 相当 |       |        |

■ 外径D公差:  $\varnothing 10$ 以下-0.5mm~0mm  $\varnothing 12$ 以上-0.8mm~0mm  
■ 长度L公差: 50以下 $\pm 1.5$ , 55以上 $\pm 2.5$   
压紧长度为参考值, 因批次不同会有偏差  
理论使用次数100万次

| 型号   |    | d   | 压紧长度 | Fmax  | N (kgf)<br>max |      |     |
|------|----|-----|------|-------|----------------|------|-----|
| 代码   | D  |     |      |       |                |      |     |
| AUBB | 4  | L   | 5    | 0.55  | 3.3            | 1.25 | 6.1 |
|      |    | 10  | 0.65 | 7     | 2.5            | 12.3 |     |
|      |    | 15  | 0.7  | 10.3  | 3.75           | 18.4 |     |
|      |    | 20  | 0.75 | 14.4  | 5              | 24.5 |     |
|      |    | 25  | 0.8  | 19.4  | 5              | 24.5 |     |
|      | 5  | 5   | 0.6  | 2.9   | 1.25           | 6.1  |     |
|      |    | 10  | 0.75 | 6.9   | 2.5            | 12.3 |     |
|      |    | 15  | 0.8  | 9.8   | 3.75           | 18.4 |     |
|      |    | 20  | 0.85 | 13.4  | 5              | 24.5 |     |
|      |    | 25  | 0.9  | 17.6  | 6.25           | 30.6 |     |
|      | 6  | 30  | 0.9  | 21.8  | 7.5            | 36.8 |     |
|      |    | 5   | 0.8  | 3.6   | 1.25           | 12.3 |     |
|      |    | 10  | 0.9  | 6.8   | 2.5            | 24.5 |     |
|      |    | 15  | 1    | 10.5  | 3.75           | 36.8 |     |
|      |    | 20  | 1.1  | 14.6  | 5              | 49   |     |
|      |    | 25  | 1.1  | 17.9  | 6.25           | 61.3 |     |
|      |    | 30  | 1.2  | 23.1  | 6              | 58.8 |     |
|      |    | 35  | 1.2  | 27.3  | 7              | 68.6 |     |
|      |    | 40  | 1.2  | 31.2  | 8              | 78.5 |     |
|      |    | 45  | 1.3  | 34.8  | 9              | 88.3 |     |
|      | 8  | 50  | 1.3  | 38.4  | 10             | 98.1 |     |
|      |    | 60  | 1.3  | 44.2  | 9              | 88.3 |     |
|      |    | 70  | 1.4  | 58.5  | 10.5           | 103  |     |
|      |    | 10  | 1.1  | 6.9   | 2.5            | 24.5 |     |
|      |    | 15  | 1.2  | 9.9   | 3.75           | 36.8 |     |
|      |    | 20  | 1.3  | 14    | 5              | 49   |     |
|      |    | 25  | 1.3  | 14.5  | 6.25           | 61.3 |     |
|      |    | 30  | 1.4  | 21.4  | 7.5            | 73.5 |     |
|      |    | 35  | 1.4  | 22    | 8.75           | 85.8 |     |
|      |    | 40  | 1.5  | 28.9  | 10             | 98.1 |     |
|      | 10 | 45  | 1.5  | 32.6  | 11.25          | 110  |     |
|      |    | 10  | 1.3  | 7.2   | 2.5            | 24.5 |     |
|      |    | 15  | 1.4  | 10.2  | 3.75           | 36.8 |     |
|      |    | 20  | 1.5  | 13.99 | 5              | 49   |     |
|      |    | 25  | 1.5  | 16.1  | 6.25           | 61.3 |     |
|      |    | 30  | 1.6  | 20.4  | 7.5            | 73.5 |     |
|      |    | 35  | 1.6  | 22.8  | 8.75           | 85.8 |     |
|      |    | 40  | 1.7  | 27.2  | 10             | 98.1 |     |
|      |    | 45  | 1.7  | 30.6  | 11.25          | 110  |     |
|      |    | 50  | 1.8  | 36.5  | 12.5           | 123  |     |
|      | 60 | 1.8 | 41.4 | 15    | 147            |      |     |
|      | 70 | 1.9 | 50.8 | 17.5  | 172            |      |     |

| 型号   |    | d  | 压紧长度 | Fmax | N(kgf)<br>max |      |
|------|----|----|------|------|---------------|------|
| 代码   | D  |    |      |      |               | L    |
| AUBB | 12 | 15 | 1.5  | 9.4  | 3.75          | 36.8 |
|      |    | 20 | 1.6  | 12.4 | 5             | 49   |
|      |    | 25 | 1.7  | 16.2 | 6.25          | 61.3 |
|      |    | 30 | 1.8  | 20.3 | 7.5           | 73.5 |
|      |    | 40 | 1.9  | 28   | 10            | 98.1 |
|      |    | 50 | 2    | 35.5 | 12.5          | 123  |
|      |    | 60 | 2.1  | 43.6 | 15            | 147  |
|      |    | 70 | 2.1  | 48.8 | 17.5          | 172  |
|      | 13 | 80 | 2.2  | 58.5 | 20            | 196  |
|      |    | 15 | 1.8  | 9.5  | 3.75          | 73.5 |
|      |    | 20 | 1.9  | 12.9 | 5             | 98.1 |
|      |    | 25 | 2    | 17   | 6.25          | 123  |
|      |    | 30 | 2.1  | 20.5 | 7.5           | 147  |
|      |    | 40 | 2.3  | 28   | 10            | 196  |
|      |    | 45 | 2.3  | 32.2 | 11.25         | 221  |
|      |    | 50 | 2.4  | 36   | 12.5          | 245  |
|      | 14 | 60 | 2.5  | 44.4 | 12            | 235  |
|      |    | 70 | 2.6  | 54   | 14            | 275  |
|      |    | 15 | 1.9  | 10   | 3.75          | 73.5 |
|      |    | 20 | 2    | 13.5 | 5             | 98.1 |
|      |    | 25 | 2.1  | 16.3 | 6.25          | 123  |
|      |    | 30 | 2.3  | 21.3 | 7.5           | 147  |
|      |    | 35 | 2.3  | 24.7 | 8.75          | 172  |
|      |    | 40 | 2.4  | 28.2 | 10            | 196  |
|      | 16 | 60 | 2.6  | 43.6 | 15            | 294  |
|      |    | 80 | 2.7  | 61.4 | 16            | 314  |
|      |    | 15 | 2    | 10   | 3.75          | 73.5 |
|      |    | 20 | 2.1  | 12.1 | 5             | 98.1 |
|      |    | 25 | 2.3  | 17.3 | 6.25          | 123  |
|      |    | 30 | 2.4  | 21   | 7.5           | 147  |
|      |    | 35 | 2.5  | 24.4 | 8.75          | 172  |
|      |    | 40 | 2.6  | 28   | 10            | 196  |
|      | 20 | 45 | 2.7  | 31.7 | 11.25         | 221  |
|      |    | 50 | 2.7  | 35.8 | 12.5          | 245  |
|      |    | 60 | 2.9  | 43.5 | 15            | 294  |
|      |    | 70 | 2.9  | 49.4 | 17.5          | 343  |
|      |    | 80 | 3    | 59.3 | 16            | 314  |
|      |    | 25 | 2.9  | 16.7 | 6.25          | 184  |
|      |    | 30 | 3    | 20.3 | 7.5           | 221  |
|      |    | 35 | 3    | 22.7 | 8.75          | 257  |
|      |    | 40 | 3.2  | 27.2 | 10            | 294  |
|      |    | 45 | 3.2  | 29.6 | 9             | 265  |
|      |    | 50 | 3.4  | 38.3 | 10            | 294  |
|      |    | 60 | 3.5  | 44.6 | 12            | 353  |

■ AUBB: Fmax(容许位移量) = L $\times$ (15~25)%



请按图示订货

## ■ AUBB-D4-L10

型号

| 代码   | D | L       |
|------|---|---------|
| AUBB | 4 | 5<br>10 |



交期Delivery

5天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌, 让采购更便捷, 让设计更高效!