


压缩弹簧 ◀ 外径基准型(不锈钢)



代码	类型	材质		允许位移量	弹簧常数公差
		国标	相当		
AUL	外径基准 不锈钢型	OCr18Ni9	SUS304-WPB	$L \times 40\%$	$\pm 10\%$
AUTT				$L \times (27\sim 40)\%$	

■ 外径D公差 $\phi 10$ 以下-0.5mm~0mm $\phi 12$ 以上-0.8mm~0mm
长度L公差50以下 ± 1.5 , 55以上 ± 2.5
压紧长度为参考值, 因批次不同会有偏差, 理论使用次数100万次。
AUL-D2,AUL-D3,AUL-D4-L5~L35,AUL-D5-L5~L25,AUL-D6-L5~L15
规格两端均未进行磨削加工。
AUTT-D3,AUTT-D4-L5~L20,AUTT-D5-L5~L10,AUTT-D6-L5
规格两端均未进行磨削加工。

型号		D	L	d	压紧长度	Fmax	N(kgf) max
代码							
AUL	2	5	0.2	1.65	2	0.98	
		10	0.26	5.07	4	1.96	
		15	0.26	5.07	6	2.94	
		20	0.3	9.9	8	3.92	
		25	0.32	14.1	10	4.9	
		30	0.32	14.1	12	5.88	
	3	5	0.3	2	2	2	
		10	0.35	3.7	4	3.9	
		15	0.4	6.6	6	5.9	
		20	0.4	6.6	8	7.8	
		25	0.45	11.7	10	9.8	
		30	0.45	11.7	12	11.8	
	4	5	0.35	2.1	2	2	
		10	0.45	5.3	4	3.9	
		15	0.45	5.3	6	5.9	
		20	0.5	8	8	7.8	
		25	0.5	8	10	9.8	
		30	0.55	12.7	12	11.8	
	5	5	0.4	2.2	2	2	
		10	0.5	4.75	4	3.9	
		15	0.5	4.75	6	5.9	
		20	0.55	6.88	8	7.8	
		25	0.55	6.88	10	9.8	
		30	0.65	14.95	12	11.8	
	6	5	0.45	2.3	2	2	
		10	0.55	4.4	4	3.9	
		15	0.55	4.4	6	5.9	
		20	0.65	8.5	8	7.8	
		25	0.65	8.5	10	9.8	
		30	0.7	12.6	12	11.8	
	8	5	0.75	17.3	20	19.6	
		60	0.8	24.8	24	23.5	
		70	0.8	24.8	28	27.5	
		10	0.65	4.6	4	3.9	
		15	0.75	8.3	6	5.9	
		20	0.75	8.3	8	7.8	

型号		D	L	d	压紧长度	Fmax	N(kgf) max
代码							
AUL	10	10	0.75	4.7	4	3.9	
		15	0.8	6.2	6	5.9	
		20	0.8	6.2	8	7.8	
		25	0.9	9.5	10	9.8	
		30	0.9	9.5	12	11.8	
		35	0.9	9.5	14	13.7	
	12	40	1	15.5	16	15.7	
		45	1	15.5	18	17.7	
		50	1	15.5	20	19.6	
		60	1.1	23.7	24	23.5	
		70	1.1	23.7	28	27.5	
		80	1.1	23.7	32	31.4	
	13	15	0.9	6.75	6	5.9	
		20	1	10	8	7.8	
		25	1	10	10	9.8	
		30	1.1	14.85	12	11.8	
		35	1.1	14.85	14	13.7	
		40	1.2	21.6	16	15.7	
	16	45	1.2	21.6	18	17.7	
		50	1.2	21.6	20	19.6	
		60	1.3	32.5	24	23.5	
		70	1.3	32.5	28	27.5	
		80	1.4	46.2	32	31.4	
	20	15	0.9	5.4	6	5.9	
		20	1	8.25	8	7.8	
		25	1	8.25	10	9.8	
		30	1.1	12.1	12	11.8	
		35	1.1	12.1	14	13.7	
		40	1.1	12.1	16	15.7	

■ AUL: Fmax(容许位移量) = $L \times 40\%$



压缩弹簧 ◀ 外径基准型(不锈钢)

弹簧／氮气弹簧 33

型号			d	压紧长度	Fmax	N(kgf) max
代码	D	L				
AUTT	3	5	0.35	2.8	2	2.9
		10	0.4	4.8	4	5.9
		15	0.45	8.3	6	8.8
		20	0.45	8.3	6	8.8
		25	0.5	14	8	11.8
		30	0.5	14	8	11.8
	4	5	0.4	2.6	2	2.9
		10	0.45	3.9	4	5.9
		15	0.5	6	6	8.8
		20	0.55	9.4	8	11.8
		25	0.6	14.4	10	14.7
		30	0.6	14.4	10	14.7
	5	5	0.45	2.6	2	2.9
		10	0.5	3.6	4	5.9
		15	0.6	7.5	6	8.8
		20	0.6	7.5	8	11.8
		25	0.65	10.7	10	14.7
		30	0.7	15.4	12	17.7
	6	35	0.7	15.4	14	20.6
		5	0.5	2.4	2	3.9
		10	0.6	4.2	4	7.8
		15	0.7	7.4	6	11.8
		20	0.7	7.4	8	15.7
		25	0.8	13.6	10	19.6
		30	0.8	13.6	12	23.5
		35	0.85	17.5	14	27.5
		40	0.9	23.4	16	31.4
		45	0.9	23.4	18	35.3
	8	50	0.9	23.4	18	35.3
		60	1	41	18	35.3
		70	1	41	24	47.1
		10	0.75	5.3	4	7.8
		15	0.75	5.3	6	11.8
		20	0.9	10.4	8	15.7
		25	0.9	10.4	10	19.6
		30	1	17	12	23.5
		35	1	17	14	27.5
		40	1	17	16	31.4
		45	1.1	25.3	18	35.3
		50	1.1	25.3	20	39.2
		60	1.1	25.3	24	47.1
		70	1.2	39.6	28	54.9

型号			d	压紧长度	Fmax	N(kgf) max
代码	D	L				
AUTT	10	10	0.85	5.1	4	7.8
		15	0.85	5.1	6	11.8
		20	1	9.5	8	15.7
		25	1	9.5	10	19.6
		30	1.1	14.3	12	23.5
		35	1.1	14.3	14	27.5
		40	1.2	20.4	16	31.4
		45	1.2	20.4	18	35.3
		50	1.2	20.4	20	39.2
		60	1.3	29.9	24	47.1
	13	70	1.4	43.4	24	47.1
		15	1	5.75	6	11.8
		20	1.2	10.5	8	15.7
		25	1.2	10.5	10	19.6
		30	1.3	15	12	23.5
		35	1.3	15	14	27.5
		40	1.4	20.3	16	31.4
		45	1.4	20.3	18	35.3
		50	1.5	27.8	20	39.2
		60	1.5	27.8	24	47.1
	16	70	1.6	38.4	28	54.9
		80	1.6	38.4	32	62.8
		15	1.2	7.2	6	11.8
		20	1.3	9.1	8	15.7
		25	1.3	9.1	10	19.6
		30	1.4	12.3	12	23.5
		35	1.5	16.5	14	27.5
		40	1.6	21.6	16	31.4
		45	1.6	21.6	18	35.3
		50	1.7	28	20	39.2
	20	60	1.7	28	24	47.1
		70	1.8	36	28	54.9
		80	1.8	36	32	62.8
		20	1.7	10.6	8	31.4
		25	1.8	12.6	10	39.2
		30	1.8	12.6	12	47.1
		35	2	19	14	54.9
		40	2	19	16	62.8
		45	2	19	18	70.6
		50	2.2	27.5	20	78.5
		60	2.2	27.5	24	94.1
		70	2.3	34.5	28	109.8
		80	2.4	40.8	32	125.5

■AUTT: Fmax(容许位移量)=LX(27~40)%



请按图示订货

■AUTT-D5-L15

型号		
代码	D	L
AUTT	5	15 20



交期Delivery

5天

发货

○本产品发货时间不含周日



www.vipdo.cn



400-098-1117

工厂自动化零件一站式采购平台