


压缩弹簧 ◀ 外径基准型 (弹簧钢)





代码	类型	材质		表面处理	允许位移量	弹簧常数公差
		国标	相当			
AWH	外径基准型	琴钢丝	SWP	发黑	L×(20~30)%	±10%

■ 外径D公差: φ10以下-0.5mm~0mm φ12以上-0.8mm~0mm
■ 长度L公差: 50以下±1.5, 55以上±2。
压紧长度为参考值, 因批次不同会有偏差, 理论使用次数100万次。
AWH-D4-L5~L10,AWH-D5-L5,AWH-D6-L5规格两端均未进行磨削加工。

■ 技术参数表						
型号						
代码	D	L	d	压紧长度	Fmax	N (kgf) max
AWH	4	5	0.45	2.7	1.5	4.9
		10	0.45	2.7	3	8.8
		15	0.55	5.8	4.5	13.7
		20	0.6	8.4	6	17.7
		25	0.65	12.4	7.5	22.6
		30	0.65	12.4	9	26.5
	5	5	0.6	3.3	1.5	8.8
		10	0.7	5.5	3	17.7
		15	0.75	7.5	4.5	26.5
		20	0.75	7.5	6	35.3
		25	0.85	13.6	7.5	44.1
		30	0.85	13.6	7.5	44.3
	6	5	0.9	17.1	8.8	51.6
		40	0.9	17.1	8.8	51.9
		5	0.65	3.3	1.5	8.8
		10	0.75	5.2	3	17.7
		15	0.8	6.4	4.5	26.5
		20	0.9	9.9	6	35.3
	8	25	0.9	9.9	7.5	44.1
		30	1	16	9	53
		35	1	16	10.5	61.8
		40	1.1	25	12	70.6
		45	1.1	25	11.3	66.7
		50	1.2	39.6	10	58.8

型号						
代码	D	L	d	压紧长度	Fmax	N (kgf) max
AWH	8	40	1.2	16.8	12	70.6
		45	1.3	24.7	13.5	79.4
		50	1.3	24.7	15	88.3
		55	1.4	35	16.5	97.1
		60	1.4	35	18	105.9
		65	1.4	35	17	100
	10	70	1.4	35	19	111.8
		10	1	5.4	3	17.7
		15	1.1	7	4.5	26.5
		20	1.2	9.6	6	35.3
		25	1.2	9.6	7.5	44.1
		30	1.3	13.9	9	53
	12	35	1.4	18	10.5	61.8
		40	1.4	18	12	70.6
		45	1.5	25	13.5	79.4
		50	1.5	25	15	88.3
		55	1.5	25	16.5	97.1
		60	1.5	25	18	105.9

压缩弹簧 ◀ 外径基准型 (弹簧钢)

型号						
代码	D	L	d	压紧长度	Fmax	N (kgf) max
AWH	13	10	1.3	6.2	3	29.4
		15	1.5	9.3	4.5	44.1
		20	1.6	12.3	6	58.8
		25	1.6	12.3	7.5	73.5
		30	1.7	15	9	88.3
		35	1.7	15	10.5	103
		40	1.8	19	12	117.7
		45	1.9	25	13.5	132.4
		50	1.9	25	15	147.1
		55	2	30	16.5	161.8
		60	2	30	18	176.5
		65	2.1	39	19.5	191.2
	14	70	2.1	39	21	205.9
		80	2.1	39	24	235.4
		15	1.6	10.4	4.5	44.1
		20	1.6	10.4	6	58.8
		25	1.6	10.4	7.5	73.5
		30	1.7	12.8	9	88.3
		35	1.7	12.8	10.5	103
		40	1.9	20	12	117.7
		45	1.9	20	13.5	132.4
		50	2.1	30.5	15	147.1
		55	2.1	30.5	16.5	161.8
	16	60	2.1	30.5	18	176.5
		65	2.2	37.4	19.5	191.2
		70	2.2	37.4	21	205.9
		80	2.3	47.2	24	235.4
		15	1.7	10.2	4.5	44.1
		20	1.8	12.6	6	58.8
		25	1.9	14.5	7.5	73.5
		30	1.9	14.5	9	88.3
		35	2	18	10.5	103
		40	2.1	21	12	117.7
		45	2.2	26	13.5	132.4
	18	50	2.2	26	15	147.1
		55	2.2	26	16.5	161.8
		60	2.3	32	18	176.5
		65	2.3	32	19.5	191.2
		70	2.4	38	21	205.9
		80	2.5	47.5	24	235.4
		20	2.1	12.6	6	88.3
		25	2.2	15.4	7.5	109.8
		30	2.2	15.4	9	132.4
		35	2.3	18.4	10.5	154
		40	2.4	21.6	12	176.5
		45	2.5	25	13.5	199.1
	20	50	2.5	25	15	220.6
		55	2.6	30	16.5	242.2
		60	2.6	30	18	264.8
		65	2.8	42	19.5	286.4
		70	2.8	42	21	308.9
		80	2.9	49.3	24	353
		90	3	57	26.1	397.2
		100	3	57	24	441.3
	22	20	2.3	12.7	6	88.3
		25	2.3	15	7.5	109.8
		30	2.3	15	9	132.4
		35	2.5	20	10.5	154
		40	2.5	20	12	176.5
		45	2.5	20	13.5	199.1
		50	2.6	22.8	15	220.6
		55	2.6	22.8	16.5	242.2
		60	2.8	30.8	18	264.8
		65	2.8	30.8	19.5	286.4
		70	3	42	21	308.9
		80	3	42	24	353
	27	90	3.2	56.8	27	397.2
		100	3.2	56.8	30	441.3
		20	2.3	12.7	6	88.3
		25	2.5	16.7	7.5	109.8
		30	2.5	16.7	9	132.4
		35	2.6	18.2	10.5	154
		40	2.8	25	12	176.5
		45	2.8	25	13.5	199.1
		50	2.8	25	15	220.6
		55	3	33	16.5	242.2
		60	3	33	18	264.8
		65	3	33	19.5	286.4
	28	70	3.2	43	21	308.9
		80	3.2	43	24	353
		90	3.2	43	26.1	397.2
		100	3.5	64.4	26	441.3
		30	2.8	16.8	9	132.4
		35	2.8	16.8	10.5	154
		40	2.9	18.8	12	176.5
		45	2.9	19.4	13.5	199.1
		50	3.2	25.5	15	220.6
		55	3.2	25.5	16.5	242.2
		60	3.5	35.5	18	264.8
		65	3.5	35.5	19.5	286.4
		70	3.5	35.5	21	308.9
		80	3.5	35.5	24	353
		90	3.5	35.5	27	397.2
		100	4	68	30	441.3

■ AWH: Fmax(容许位移量) =LX (20~30)%



请按图示订货

■ AWH-D4-L10

型号		
代码	D	L
AWH	5	15 20



交期Delivery

5天	发货
----	----

○ 本产品发货时间不含周日