


压缩弹簧 ◀ 外径基准型(不锈钢)



■ 外径D公差: $\varnothing 10$ 以下-0.5mm~0mm
 $\varnothing 13$ 以上-0.8mm~0mm
■ 长度L公差: 50以下 ± 1.5 , 55以上 ± 2.5
压紧长度为参考值, 因批次不同会有偏差。
理论使用次数100万次
两端均未进行磨削加工。

代码	类型	材质		允许位移量	弹簧常数公差	表面处理
		国标	相当			
AWY	外径基准型	琴钢丝	SWP	$L \times 75\%$	$\pm 10\%$	发黑

型号		d	压紧长度	Fmax	N(kgf) max
代码	D				
AWY	3	5	0.16	1	3.75
		10	0.2	2	7.5
		15	0.23	3.6	11.2
		20	0.23	3.6	15
		25	0.25	5.5	18.7
		30	0.26	6.5	22.5
	4	5	0.2	1.1	3.75
		10	0.23	1.9	7.5
		15	0.23	1.9	11.2
		20	0.25	2.7	15
		25	0.29	5	18.7
		30	0.29	5	22.5
	5	10	0.25	1.7	7.5
		15	0.25	1.7	11.2
		20	0.3	3.2	15
		25	0.3	3.2	18.7
		30	0.35	6.3	22.5
		35	0.35	6.3	26.2
	6	40	0.38	9.2	30
		45	0.38	9.2	33.7
		50	0.38	9.2	37.5
		10	0.3	2.1	7.5
		15	0.32	2.8	11.2
		20	0.32	2.8	15
	8	25	0.35	4.1	18.7
		30	0.38	5.6	22.5
		35	0.38	5.6	26.2
		40	0.4	7.2	30
		45	0.4	7.2	33.7
		50	0.4	7.2	37.5
	10	55	0.45	12.2	41.2
		60	0.45	12.2	45
		65	0.45	12.2	48.7
		70	0.45	12.2	52.5
		10	0.35	2.1	7.5
		15	0.38	3	11.2
	12	20	0.4	3.5	15
		25	0.4	3.5	18.7
		30	0.45	5.7	22.5
		35	0.45	5.7	26.2
		40	0.45	5.7	30
		45	0.45	5.7	33.7

型号		d	压紧长度	Fmax	N(kgf) max
代码	D				
AWY	8	45	0.45	5.7	33.7
		50	0.5	9	37.5
		55	0.5	9	41.2
		60	0.5	9	45
		65	0.5	9	48.7
		70	0.5	9	52.5
	10	15	0.5	3	11.2
		20	0.55	4.6	15
		25	0.55	4.6	18.7
		30	0.6	6.6	22.5
		35	0.6	6.6	26.2
		40	0.65	9.1	30
	12	45	0.65	9.1	33.7
		50	0.65	9.1	37.5
		55	0.7	12.6	41.2
		60	0.7	12.6	45
		65	0.7	12.6	48.7
		70	0.7	12.6	52.5
	14	20	0.6	3.9	15
		25	0.65	5.1	18.7
		30	0.65	5.1	22.5
		35	0.7	6.7	26.2
		40	0.75	8.7	30
		45	0.75	8.7	33.7
	16	50	0.8	11.6	37.5
		55	0.8	11.6	41.2
		60	0.8	11.6	45
		65	0.85	15.3	48.7
		70	0.85	15.3	52.5
		20	0.65	3.6	15
	18	25	0.7	4.6	18.7
		30	0.75	5.7	22.5
		35	0.8	7	26.2
		40	0.85	9	30
		45	0.85	9	33.7
		50	0.9	11.3	37.5
	20	55	0.9	11.3	41.2
		60	0.9	11.3	45
		65	0.9	11.3	48.7
		70	0.9	11.3	52.5
		10	0.35	2.1	7.5
		15	0.38	3	11.2

■ AWY: Fmax(容许位移量) = $L \times 75\%$



请按图示订货

■ AWY-D3-L10

型号

代码

D

L

AWY

3

5

10



交期Delivery

4天

发货

○ 本产品发货时间不含周日