

高扭矩圆弧齿同步带轮 ◀ HTDH5M型(齿距5)






型号				材质		表面处理
皮带宽度9mm	皮带宽度15mm	皮带宽度25mm	皮带宽度30mm	带轮	法兰	
A:11 W:16	A:17 W:22	A:27 W:32	A:32 W:37	铝合金		本色阳极氧化
VPT01□□H5M090	VPT21□□H5M150	VPT31□□H5M250	VPT41□□H5M300			黑色阳极氧化
VPT02□□H5M090	VPT22□□H5M150	VPT32□□H5M250	VPT42□□H5M300			喷砂无电解镀锌
VPT03□□H5M090	VPT23□□H5M150	VPT33□□H5M250	VPT43□□H5M300			发黑
VPT04□□H5M090	VPT24□□H5M150	VPT34□□H5M250	VPT44□□H5M300	S45C	SPCC	无电解镀锌
VPT05□□H5M090	VPT25□□H5M150	VPT35□□H5M250	VPT45□□H5M300			

带轮形状: A形

带轮形状: B形

标准齿形



铝合金材质时: $t_1 = (w-a)/2 - 0.5$, S45C材质时: $t_1 = 1.5$

■轴孔规格

H 圆孔





P 圆孔+螺孔

N 新JIS键槽孔+螺孔
C 旧JIS键槽孔+螺孔

V 台阶孔

F 台阶孔(轮毂侧沉孔)

Y 两端台阶孔



键槽尺寸详见
同步轮产品简介

K 形不适用

仅适用于B形

仅适用于A形

■轴孔P.N.C螺孔尺寸表

轴孔内径dH7	M	附件紧固螺钉
5	M3	M3×3
6~12	M4	M4×3
13~17	M5	M5×4
18~30	M6	M6×5
31~45	M8	M8×6
46~65	M10	M10×8



当同步轮材质为S45C时,
挡圈存在折边式。



视角标准: 第一视角

型号		带轮 形状	轴孔规格dH7(最小单位1)										轴孔V、F		轴孔Y (最小单位1)		P.D.	O.D.	D	F	E	带轮 公称宽度			
代码	齿数		A形					B形					Z(最小单位1)		J (最小单位0.1)	Q-R						S-T	A	W	L
			H	P	N·C	V	Y	H	P	N·C	V·F	A形	B形												
铝合金材质		14	6~10	6~10	8~10	5~6	5~6	6~10	6~8	/	5~6	7~8	7~8		7~8		22.28	21.14	14	26	16	皮带宽度9 H5M090 A:11 W:16 L:28			
VPT01-H5M090		15	6~10	6~10	8~10	6~8	6~8	6~10	6~8	/	5~8	9~10	7~10		9~10		23.87	22.73	15	28	18				
VPT02-H5M090		16	7~12	7~12	8~12	7~10	7~10	7~12	7~10	8	5~10	10~12	7~12		10~12		25.46	24.32	17	32	20				
VPT03-H5M090		18	7~14	7~12	8~12	7~12	7~12	7~14	7~11	8~10	7~12	10~14	10~14		12~14		28.65	27.51		33	22	A:11 W:16 L:28			
VPT21-H5M150		19	6~16	6~16	8~16	6~14	6~14	6~15	6~11	8~10	6~13	8~16	8~15		8~16		30.24	29.10	19		36		24		
VPT22-H5M150		20	7~16	7~16	8~16	7~14	7~14	7~15	7~11	8~10	7~13	10~16	10~15		10~16		31.83	30.69							
VPT23-H5M150		22	7~19	7~18	8~18	7~17	7~17	7~19	7~15	8~12	7~17	10~19	10~19		10~19		35.01	33.87	24	40	27	皮带宽度15 H5M150 A:17 W:22 L:34			
VPT31-H5M250		24	7~22	7~20	8~20	7~20	7~20	7~22	7~17	8~13	7~20	10~23	10~23		10~22		38.20	37.06							
VPT32-H5M250		25	7~22	7~20	8~20	7~20	7~20	7~22	7~17	8~15	7~20	10~23	10~23		10~22		39.79	38.65	27	45	30				
VPT33-H5M250		26	8~27	8~22	8~22	8~25	8~25	8~27	8~21	8~17	8~25	11~27	11~27		11~27	3~14 S+T≤W-3	41.38	40.24	31		48	35	皮带宽度25 H5M250 A:27 W:32 L:44		
VPT41-H5M300		28	8~27	8~24	8~24	8~24	8~24	8~27	8~22	8~18	8~25	11~27	11~27		11~27		44.56	43.42	32						
VPT42-H5M300		30	10~28	10~26	10~26	10~26	10~26	10~28	10~23	10~18	10~25	13~28	13~28		15~28		47.75	46.61	33	52	36				
VPT43-H5M300		32	10~32	10~28	10~28	10~30	10~30	10~32	10~27	10~22	10~30	13~32	13~32		15~32		50.93	49.79	37	55	40	A:27 W:32 L:44			
S45C材质		34	10~37	10~30	10~30	10~35	10~35	10~36	10~30	10~25	10~34	13~37	13~36		15~37		54.11	52.97			61		45		
VPT04-H5M090		36	10~37	10~30	10~30	10~35	10~35	10~36	10~30	10~25	10~34	13~37	13~36		15~37		57.30	56.16							
VPT05-H5M090		40	10~42	10~38	10~38	10~40	10~40	10~42	10~35	10~28	10~40	13~42	13~42		15~42		63.66	62.52	47	67	50	皮带宽度30 H5M300 A:32 W:37 L:49			
VPT24-H5M150		44	12~50	12~42	12~42	12~48	12~48	12~46	12~38	12~32	12~44	15~50	15~46		18~50		70.03	68.89	50	74	58				
VPT25-H5M150		48	12~55	12~45	12~40	12~53	12~53	12~55	12~45	12~40	12~53	15~55	15~55		18~55		76.39	75.25	60	83	63				
VPT34-H5M250		50	12~59	12~45	12~43	12~57	12~57	12~59	12~45	12~43	12~57	15~59	15~59		18~59		79.58	78.44	63	87	67	A:32 W:37 L:49			
VPT35-H5M250		60	12~72	12~45	12~45	12~70	12~70	12~71	12~45	12~45	12~69	15~72	15~72		18~72		95.48	94.34	75	99	80				
VPT44-H5M300		72	12~80	12~65	12~50	12~80	12~75	12~80	12~65	12~50	12~80	14~92	14~86		12~75		114.59	113.45	90	119	100				

注意事项: ①轴孔规格H/V/F/Y时, 无螺孔。②孔径6.35仅适用轴孔规格H/P/V/F。③孔径9不适用轴孔规格N。④孔径8/9/11/13/14/17/21~29/31/32/46~49不适用轴孔规格C。⑤选购新JIS键槽孔+螺孔的轴孔 直径d10时, 键槽尺寸可选择N-d10或N-d10K(请参阅同步轮产品简介)。



请按图示订货

■VPT01-H5M090-60-A-H-d12

代码	齿型	齿数	带轮形状	轴孔规格dH7(最小单位1)				
				H	P	N	C	V
VPT01	H5M090	60	A	12~59	12~45	12~43	12~57	12~57



交期Delivery

5天

发货

本产品发货时间不含周日