



同步轮惰轮 ◀ S5M型




代码	类型	带轮类型	材质			表面处理
			主体	法兰	轴承	
VTP01	单轴承	S5M	铝合金	铝合金	钢	本色阳极氧化
VTP02	中心双轴承		S45C	SPCC		发黑
VTP03	中心双轴承		S45C	SPCC		喷砂无电解镀锌
VTH01	双轴承	S5M	铝合金	铝合金	钢	本色阳极氧化
VTH02	双轴承		S45C	SPCC		发黑
VTH03	双轴承		S45C	SPCC		无电解镀锌


单轴承



中心双轴承



双轴承



注：带*规格为中心轴承型结构

型号			P.D.	O.D.	F	E	A	W	S	轴承尺寸					
代码	齿数	带轮类型								轴承型号×数量	d	D	B		
单轴承 中心双轴承(*) VTP01 VTP02 VTP03	16	S5M100	25.46	24.5	32	20	11	16	5	606ZZ×1	6	17	6		
	18	S5M100	28.65	27.69	33	22				698ZZ×1	8	19	6		
	20	S5M100	31.83	30.87	36	24	17	22		698ZZ×1		19	6		
	★ S5M150	698ZZ×2													
	22	S5M100	35.01	34.05	40	27	11	16	4	628ZZ×1	10	24	8		
	★ S5M150	17					22	3	628ZZ×2						
	24	S5M100	38.2	37.24	45	30	11	16	4	6000ZZ×1		26	8		
	★ S5M150	17					22	3	6000ZZ×2						
	25	S5M100	39.79	38.83	45	30	11	16	4	6000ZZ×1	12	26	8		
	★ S5M150	17					22	3	6000ZZ×2						
	VTP01	26	S5M100	41.38	40.42	48	35	11	16	3.5		6200ZZ×1	12	30	9
	VTP02	S5M100	11					16	3.5	6200ZZ×1					
	VTP03	28	S5M100	44.56	43.6	48	35	17	22	6.5	6200ZZ×1	10		32	10
		S5M100	11					16	3	6201ZZ×1					
	30	S5M150	47.75	46.79	52	36	17	22	6	6201ZZ×1	12	32	10		
	S5M100	11					16		6201ZZ×1						
	32	★ S5M150	50.93	49.97	55	40	17	22	3	6000ZZ×2	10	26	8		
	36	S5M100					57.3	56.34		61	45	11	16	6201ZZ×1	12
	40	S5M100	63.66	62.7	67	50	6201ZZ×1								

型号			P.D.	O.D.	F	E	A	W	dh	轴承尺寸			
代码	齿数	带轮类型								轴承型号×数量	d	D	B
双轴承 VTH01 VTH02 VTH03	16	S5M150	25.46	24.5	32	20	17	22	15	606ZZ×2	6	17	6
		S5M250					27	32					
	18	S5M150	28.65	27.69	33	22	17	22	17	698ZZ×2	8	19	6
		S5M250					27	32					
	20	S5M150	31.83	30.87	36	24	17	22	20	608ZZ×2	10	22	7
		S5M250					27	32					
	22	S5M150	35.01	34.05	40	27	17	22	17	698ZZ×2	6	19	6
		S5M250					27	32					
	24	S5M150	38.2	37.24	45	30	17	22	13	696ZZ×2	10	22	8
		S5M250					27	32					
	25	S5M100	39.79	38.83	45	30	11	16	20	608ZZ×2	12	26	8
		S5M250					27	32					
	25A	S5M100	39.79	38.83	45	30	17	22	15	606ZZ×2	15	28	9
		S5M250					27	32					
	26	S5M150	41.38	40.42	48	35	17	22	25	6200ZZ×2	18	30	9
		S5M250					27	32					
	28	S5M100	44.56	43.6	48	35	11	16	25	6900ZZ×2	20	32	10
		S5M250					27	32					
	30	S5M150	47.75	46.79	52	36	17	22	27	6001ZZ×2	22	32	10
		S5M250					27	32					
	32	S5M150	50.93	49.97	55	40	17	22	25	6201ZZ×2	24	32	10
		S5M250					27	32					
	36	S5M150	57.3	56.34	61	45	17	22	29	6002ZZ×2	26	35	11
		S5M250					27	32					
	40	S5M150	63.66	62.7	67	50	17	22	30	6202ZZ×2	28	35	11
		S5M250					27	32					



请按图示订货

■ VTH03-40-S5M250

型号		带轮类型
代码	齿数	
VTH03	40	S2M150 S2M250



交期Delivery

5天

发货

本产品发货时间不含周日