



代码			D 公差	材质	硬度	表面处理	
标准型	精密型	同径型					
GBM51	GBM71	GBN51	g6	GB:GCr15 JIS:相当于SUJ2	高频淬火 含有效硬化层 淬火硬度 Gcr15, HRC56~ S45C HRC56~ 9Cr18Mo HRC54~	/	
GBM52	GBM72	GBN52				镀硬铬, 镀层硬度HV850~, 镀层厚度3~5μm	
GBM56	GBM76	GBN56				/	
GBM57	GBM77	GBN57				GB:9Cr18Mo JIS:相当于SUS440C	镀硬铬, 镀层硬度HV850~, 镀层厚度3~5μm

标准型 精密型  
GBM51 GBM71  
GBM52 GBM72  
GBM56 GBM76  
GBM57 GBM77

同径型  
GBN51 GBN52  
GBN56 GBN57

导向轴 01

型号	最小单位1		M	C		
	Dg6	L			G	
同径型 GBN51 GBN52 GBN56 GBN57	4	-0.004	20~300	4~25	4	0.2
	5	-0.012	20~400	4~30	5	
	6		20~600	5~35	6	
	8	-0.005	20~800	7~45	8	0.5
	10	-0.014		8~55	10	
	12	-0.006	20~1000	9~65	12	
16	-0.017	20~1200	10~85	16	1	
20	-0.007		13~105	20		
30	-0.020	20~1500	18~155	30		

■GBN51-D4-L200-G20

型号	Dg6	L	G
GBN51	4	-0.004 -0.012	20~300 4~25

请按图示订货

交期Delivery 4天 发货

○本产品发货时间不含周日

代码	型号		(最小单位1)			P 选择	C
	Dg6	L	X	G			
标准型 GBM51 GBM52 GBM56 GBM57	4	-0.004	20~300	X=2~P×5	根据使用 要求指定	3	0.2
	5	-0.012	20~400			3 4	
	6		20~600			3 4 5 6	
	8	-0.005	20~800			4 5 6 8	0.5
	10	-0.014				5 6 8 10	
	12		20~1000			5 6 8 10 12	
	13	-0.006				5 6 8 10 12	
	15	-0.017				5 6 8 10 12	
	16		20~1200			5 6 8 10 12	
	18					6 8 10 12 16	
	20	-0.007				8 10 12 16	
	25	-0.020	20~1500			8 10 12 16 20 24	1
	30					8 10 12 16 20 24	
	35	-0.009				10 12 16 20 24 30	
	40	-0.025				12 16 20 24 30	
50		16 20 24 30					
精密型 GBM71 GBM72 GBM76 GBM77	5	-0.004	20~300	X=2~P×5	根据使用 要求指定	3	0.2
	6	-0.012	20~300			3 4	
	8	-0.005	20~350			3 4 5 6	
	10	-0.014				4 5 6 8	
	12					5 6 8 10	0.5
	13	-0.006	5 6 8 10				
	15	-0.017	5 6 8 10 12				
	16		5 6 8 10 12				
	18		5 6 8 10 12 16				
	20	-0.007	25~450			6 8 10 12 16	
	25	-0.020				8 10 12 16 20	
	30					8 10 12 16 20 24	