


定位销 ◀ 螺栓固定型 引导型





代码	类型	公差等级	材质		硬度	表面处理
			国标	相当		
MEK04	引导型	Dg6	9CrWMn	SKS3	淬火硬度58-61HRC	/
MEK05					淬火硬度58-61HRC 镀层硬度850HV~	镀硬铬, 镀层厚度3-5um
MEK06					淬火硬度HRC56~, 镀层硬度850HV~	

MEK04/05



MEK06



■ D尺寸公差

P	g6
10	-0.005 -0.014
12-16	-0.006 -0.017
20-30	-0.007 -0.020

型号			P	d1	d2	H	B	L	适用螺栓
代码	Dg6								
MEK04 MEK05 MEK06	6	-0.004	10	3.5	6.5	4	10	5	M3
		-0.012							M4
		-0.005							M5
	8	-0.014	12	4.5	8	5			M6
	10	-0.006	15	5.5	9.5	6			M8
	12	-0.017	16	6.5	11	7			M10
	15	-0.007	20	6.5	11	7	15	10	M12
	16			9	14	9			
	20			11	17.5	11			
25	-0.020	30	14	20	13				



请按图示订货

■ MKE04-D6

型号		
代码	D	P
MEK04	6	10



交期Delivery

5天

发货

○本产品发货时间不含周日