




定位销 ◀ 圆型 P尺寸选择型



P尺寸选择型			材质		硬度	表面处理		
Dm6	Dp6	Dg6	国标	相当				
MEL01	MEL07	/	9CrWMn	SKS3	淬火硬度58~61HRC	/		
MEL02	MEL08				淬火硬度58~61HRC， 镀层硬度850HV~	镀硬铬，镀层厚度3~5μm		
MEL03	MEL09				/	/		
MEL04	MEL10		0Cr18Ni9	SUS304	镀层硬度850HV~	镀硬铬，镀层厚度5~8μm		
MEL05	MEL11				9Cr18Mo	SUS440C	淬火硬度48~53HRC	/
MEL06	MEL12		/	/	MEL13	GCr15	SUJ2	淬火硬度HRC56~， 镀层硬度850HV~

MEL01/02/03/04/05/06
MEL07/08/09/10/11/12

MEL13



■ P尺寸公差表

P	g6
1.50~3	-0.002 -0.008
3.01~6	-0.004 -0.012
6.01~10	-0.005 -0.014
10.01~18	-0.006 -0.017
18.01~20	-0.007 -0.020

■ SUS440C材质的D部加工有识别槽。

代码	技术说明
RC	<p>变更颈部退刀槽为R0.5</p> <p>D-P ≤ 2不适用</p>

代码	技术说明																												
EC()	<p>变更前端锥角部长度 变更E尺寸</p> <p>最小单位1 圆锥小头直径1min B尺寸因EC的变化而变化</p> <table border="1"> <thead> <tr> <th>D</th> <th>EC</th> <th>D</th> <th>EC</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1</td> <td>8</td> <td>4~13</td> </tr> <tr> <td>3</td> <td>1~3</td> <td>10</td> <td>4~16</td> </tr> <tr> <td>4</td> <td>2~5</td> <td>12</td> <td>4~20</td> </tr> <tr> <td>5</td> <td>3~7</td> <td>13</td> <td>4~21</td> </tr> <tr> <td>6</td> <td>3~9</td> <td>16</td> <td>5~22</td> </tr> <tr> <td></td> <td></td> <td>20</td> <td></td> </tr> </tbody> </table>	D	EC	D	EC	2	1	8	4~13	3	1~3	10	4~16	4	2~5	12	4~20	5	3~7	13	4~21	6	3~9	16	5~22			20	
D	EC	D	EC																										
2	1	8	4~13																										
3	1~3	10	4~16																										
4	2~5	12	4~20																										
5	3~7	13	4~21																										
6	3~9	16	5~22																										
		20																											

型号		D公差			P	L	B	C	E	V
代码	D	m6	p6	g6						
P尺寸选择型	2	+0.008	+0.012	-0.002	1 2	4	2	0.3	0.5	0
	3	+0.002	+0.006	-0.008	1 2 3					
	4	+0.012	+0.020	-0.004	2 3 4					
Dm6 Dp6	5	+0.004	+0.012	-0.012	2 3 4 5	5	3	0.5	1	1
MEL01 MEL07	6	+0.015	+0.024	-0.005	2 3 4 5 6					
MEL02 MEL08	8	+0.006	+0.015	-0.014	3 4 5 6 8	10	5	1	2	1
MEL03 MEL09	10	+0.018	+0.029	-0.006	3 4 5 6 8 10					
MEL04 MEL10	12	+0.007	+0.018	-0.017	4 5 6 8 10 12					
MEL05 MEL11	13	+0.021	+0.035	-0.007	5 6 8 10 12 13	15	6	1.5	3	2
MEL06 MEL12	16	+0.008	+0.022	-0.020	8 10 12 13 14 15 16					
Dp6 MEL13	20				12 13 14 15 16 20	22	8	2	4	2
						30	10	3		



请按图示订货

■ MEL01-D2-P2-RC

型号	D公差				P	可选加工代码
代码	D	m6	p6	g6		
MEL01	2	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	1 2	RC



交期Delivery

5天

发货

○本产品发货时间不含周日