




定位销 ◀ 圆型 P.L.B尺寸指定型



P.L.B尺寸指定型			材质		硬度	表面处理
Dm6	Dp6	Dg6	国标	相当		
MEL14	MEL20	/	9CrWMn	SKS3	淬火硬度58~61HRC	镀硬铬, 镀层厚度3~5μm
MEL15	MEL21				淬火硬度58~61HRC, 镀层硬度850HV~	
MEL16	MEL22				/	
MEL17	MEL23				/	
MEL18	MEL24				0Cr18Ni9	
MEL19	MEL25	9Cr18Mo	SUS440C	淬火硬度48~53HRC	/	
/	/	MEL26	GCr15	SUJ2	淬火硬度HRC56~, 镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm

MEL14/15/16/17/18/19
MEL20/21/22/23/24/25

MEL 26



■ P尺寸公差表

P	g6
1.50~3	-0.002 -0.008
3.01~6	-0.004 -0.012
6.01~10	-0.005 -0.014
10.01~18	-0.006 -0.017
18.01~20	-0.007 -0.020

a=0.4 (P=2)
a=0.8 (P≥3)
d=0.05 (P=2)
d=0.1 (P≥3)

■ SUS440C材质的D部加工有识别槽。

代码	技术说明
RC	变更颈部退刀槽为R0.5 D-P≤2不适用

代码	技术说明																												
EC()	变更前端锥角部长 变更E尺寸 最小单位1 圆锥小头直径1min B尺寸因EC的变化而变化 <table border="1"> <thead> <tr> <th>D</th> <th>EC</th> <th>D</th> <th>EC</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1</td> <td>8</td> <td>4~13</td> </tr> <tr> <td>3</td> <td>1~3</td> <td>10</td> <td>4~16</td> </tr> <tr> <td>4</td> <td>2~5</td> <td>12</td> <td>4~20</td> </tr> <tr> <td>5</td> <td>3~7</td> <td>13</td> <td>4~21</td> </tr> <tr> <td>6</td> <td>3~9</td> <td>16</td> <td>5~22</td> </tr> <tr> <td></td> <td></td> <td>20</td> <td></td> </tr> </tbody> </table>	D	EC	D	EC	2	1	8	4~13	3	1~3	10	4~16	4	2~5	12	4~20	5	3~7	13	4~21	6	3~9	16	5~22			20	
D	EC	D	EC																										
2	1	8	4~13																										
3	1~3	10	4~16																										
4	2~5	12	4~20																										
5	3~7	13	4~21																										
6	3~9	16	5~22																										
		20																											

型号	D公差			最小单位0.01	最小单位1	最小单位0.1	C	E	V
	D	m6	p6						
P.L.B尺寸指定型	2	+0.008	+0.012	-0.002	1.00~2.00	2~6	0.3	0.5	0
	3	+0.002	+0.006	-0.008	1.00~3.00	3~10	0.5		
Dm6 Dp6	4	+0.012	+0.020	-0.004	1.50~4.00	4~12	1	1	1
MEL14 MEL20	5	+0.004	+0.012	-0.012	2.00~5.00	5~15		2	
MEL15 MEL21	6				2.00~6.00	5~18	1.5	3	2
MEL16 MEL22	8	+0.015	+0.024	-0.005	3.00~8.00	6~22			
MEL17 MEL23	10	+0.006	+0.015	-0.014	3.00~10.00	8~24	2	4	2
MEL18 MEL24	12	+0.018	+0.029	-0.006	5.00~12.00	10~26			
MEL19 MEL25	13	+0.007	+0.018	-0.017	6.00~13.00	12~28	3		
	16				10.00~16.00	13~35			
Dp6 MEL26	20	+0.021	+0.035	-0.007	13.00~20.00	16~42	3		

☎ 请按图示订货

■ MEL14-D2-P2-L6-B6-RC

型号	D公差			最小单位0.01	最小单位1	最小单位0.1	可选加工代码	
代码	D	m6	p6	g6	P	L	B	
MEL14	2	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	1.00~2.00	2~6	2.0~15.0	RC

🚚 交期Delivery

5天 发货

○本产品发货时间不含周日